	۵	т 	m	D		0	Ξ	Þ		7
	ØS-									4
						LAYOUT SHOWN				3
		Keying Shown as examp								
CHARACTERISTICS										
-Standard : Based on MIL-DTL-38999	Series III	Di	Connector dimension							
-Shell Material : Aluminium -Shell Plating : Black Zinc I -Insulator : Thermopla -Contacts : Copper Alle	Nickel stic		óS 25 Max Z 31 Max IREAD M15x1-6g			SOURIAU shall not be liable fo due to a use of the Product the Specifications issued by eith (professional recomme	ts which does not compl	y with third party		
-Seals & Grommet : Silicon Elas ► -Contact Plating : Gold over o	tomer copper Alloy 0.8μm minimum			L				on & Control List ot Listed		2
	-Durability : 500 Mating cycles					PN: 8D511Z22PBL				
-Temperature Range -65°C to +:	175°C			A	18-10-2016	First Release				-
-Salt Spray : 500 hours 	0%			ISS Desig	DATE ned By:	Latest modification - by Date:	C		MOD N°	
					TITLE	Aluminium Plug 8D series				
BASIC SERIES:		22 P B L	Delivered W/O		CALE -[·	General line Tolerance ±		NPRDS / PROJECT 859		-
CONTACT TYPE : Standard Crimp C SHELL SIZE : 11	CONTACT TYPE : Standard Crimp Contact ORIENTATION : B					OURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			d or	
PLATING : Z = Black Zinc Nicl	kel	L	CONTACT LAYOU	IT : 11-22 FO	RMAT		AU DRG N°		SHEET	-
Н	G		E	D		C 8D511	Z22PBL-C	A	1/2	

r	т	۵	г	т		0	
4		Contact Layout 22*					
ς.)	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905					
N						SOURIAU shall not be due to a use of the the Specifications issued (professional re PN: 8	e Products w d by either
					A 18-10-20 ISS DATE Designed By: TITLE SCALE NA	Date:	Alumi eneral linear Folerances: ±

G

Н

F

Е

FORMAT

A3

D

С

