

## Smart 108 SPU - 8-Port Cat5 KVM Switch for Rack Environments

MODEL NUMBER: 0SU22181



### Description

Save Space and Money

From SOHO to Enterprise

### Features

- 8 Ports
- BIOS level access
- Multilayer security
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cabling
- Includes a USB to PS/2 adapter that allows you to use a USB keyboard and mouse on the console end
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Highlights

- 8 Ports
- BIOS level access
- Multilayer security
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cabling
- Includes a USB to PS/2 adapter that allows you to use a USB keyboard and mouse on the console end
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### System Requirements

Operating System

- DOS, Windows, LINUX, UNIX, MAC and all other major operating systems

Console

- VGA Monitor
- USB or PS/2 Keyboard and Mouse

Resolution

- Supports video resolutions up to 1600 x 1200 @ 75Hz

### Package Includes

- Smart 108 SPU
- USB to PS/2 Adapter
- RS232 Cable



- Power Cord
- Rackmount Hardware
- Owner's Manual

## Specifications

| OVERVIEW                        |                            |
|---------------------------------|----------------------------|
| UPC Code                        | 654518212440               |
| Console                         | No                         |
| PHYSICAL                        |                            |
| Color                           | Black                      |
| Shipping Dimensions (hwd / cm)  | 17.78 x 19.05 x 2.54       |
| Shipping Dimensions (hwd / in.) | 7.00 x 7.50 x 1.00         |
| Shipping Weight (kg)            | 1.41                       |
| Shipping Weight (lbs.)          | 3.10                       |
| Unit Dimensions (hwd / cm)      | 4.15 x 21.5 x 12.2         |
| Unit Dimensions (hwd / in.)     | 1.63 x 8.46 x 4.8          |
| Unit Weight (kg)                | 1.86                       |
| Unit Weight (lbs.)              | 4.1                        |
| ENVIRONMENTAL                   |                            |
| Storage Temperature Range       | -40 to 70 C / -40 to 158 F |
| Relative Humidity               | 80% Non-Condensing         |
| Operating Temperature           | 0 to 40 C / 32 to 104 F    |
| COMMUNICATIONS                  |                            |
| Port Control                    | Push Buttons, Hotkeys, OSD |
| IP Remote Access                | Yes                        |
| CONNECTIONS                     |                            |
| Ports                           | 8                          |
| PC/Server Connections           | VGA; USB; PS/2             |
| FEATURES & SPECIFICATIONS       |                            |
| Number of Users                 | 1                          |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |                         |
|-------------------------------------|-------------------------|
| Cat5 KVM Switch                     | Yes                     |
| <b>WARRANTY</b>                     |                         |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>