

820BYYY-203R001

SERIES _____
 POSITIONS _____
 YYY = SEE POSITION CHART
 GENDER _____
 2 = FEMALE
 TYPE _____
 0 = SOLDER CUP PANEL MOUNT
 SHELL PLATING _____
 3 = NICKEL/CHROME
 CONTACT PLATING _____
 1 = 7μ" GOLD PLATED

SPECIFICATIONS:

MATERIALS:
 SHELL: NICKEL/CHROME PLATED BRASS
 CONTACTS: 7u" GOLD PLATED BRASS
 NUT: NICKEL/CHROME PLATED BRASS
 INSULATOR: PPS (HIGH TEMPERATURE)


MECHANICAL:
 MATING CYCLES: 5000 CYCLES
 OPERATING TEMPERATURE: -40°C TO +200°C
 PROCESS TEMPERATURE: 260°C FOR 5 SECONDS
 SHIELDING: 75dB @ 10MHz // 40dB @ 1GHz
 IP RATING: 50
 MAX TORQUE: 2.5 Nm

POSITION CHART // ELECTRICAL/WIRE SPECIFICATIONS						
POSITIONS	CONTACTS	CONTACT Ø	MAX CONTACT mΩ	WORKING VOLTAGE	MAX AMPERAGE	MAX WIRE AWG
002		0.90mm	6.0 mΩ	330 V	10.0 A	22
003		0.90mm	6.0 mΩ	400 V	8.0 A	22
004		0.70mm	7.5 mΩ	280 V	7.0 A	24
005		0.70mm	7.5 mΩ	280 V	6.5 A	24
006		0.50mm	10.0 mΩ	280 V	2.5 A	28
007		0.50mm	10.0 mΩ	260 V	2.5 A	28
009		0.50mm	10.0 mΩ	200 V	2.0 A	28


RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING

 THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: M. SIGMON
 DATE: 02/05/2016



SCALE: NTS SHEET 1 OF 1 REV 4
 DWG NO. 820BYYY-203R001