


SC-10-S30JH

Aliases (UALSC10S30JH00)

KEMET, SC Three Phase, AC Line Filters, Common Mode, 3 mH



Click here for the 3D model.

Dimensions		
D	42mm MAX	
Н	27mm MAX	
LL	3.5mm +/-1mm	
S	38mm NOM	
Wire Size	1.1mm	

Packaging Specifications	
Packaging	Tray
Packaging Quantity	80
Component Weight	72 g

General Information	n
Series	SC Three Phase
Style	Through-Hole
Features	High Impedance
RoHS	Yes
Notes	Lead Spacing (S/S1) Are For Reference Only.
Miscellaneous	Temperature Rise Maximum: 120 K.
Core	Mn-Zn Ferrite

Specifications	
Voltage AC	250 VAC
Voltage DC	250 VDC
Inductance	3 mH (10 kHz)
Current	10 A
Temperature Range	-25/+120°C
DC Resistance	25 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.