



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Olive drab Cadmium
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 2000 hours
- Mass : 9.7 g ± 10%

| Connector dimension |             |
|---------------------|-------------|
| Dim                 | Nominal     |
| P                   | 3.25±0.2    |
| PP                  | 4.93±0.2    |
| R1                  | 20.62       |
| R2                  | 18.26       |
| S                   | 26.2±0.3    |
| V'                  | 19.5+1.4/-0 |
| W'                  | 2.1/3.65    |
| Z'                  | 32 Max      |
| VV THREAD           | M15x1-6g    |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D011J04PDL**

|                |                                       |                                |   |
|----------------|---------------------------------------|--------------------------------|---|
| A              | 06-10-2016                            | First Release                  |   |
| ISS            | DATE                                  | Latest modification - by       | MOD N°  |
| Designed By:   |                                       | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Composite Receptacle 8D series</b> |                                |   |
| SCALE          |                                       | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| NA             |                                       |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                                |   |
| FORMAT         | <b>SOURIAU DRG N° 8D011J04PDL-C</b>   |                                | SHEET<br>1/2  |

|                |                          |   |   |    |   |                                 |   |   |   |                        |
|----------------|--------------------------|---|---|----|---|---------------------------------|---|---|---|------------------------|
| BASIC SERIES:  | 8D                       | 0 | - | 11 | J | 04                              | P | D | L | Delivered W/O Contacts |
| SHELL TYPE :   | Square Flange Receptacle |   |   |    |   | ORIENTATION : D                 |   |   |   |                        |
| CONTACT TYPE : | Standard Crimp Contact   |   |   |    |   | CONTACT TYPE : PIN(500 Matings) |   |   |   |                        |
| SHELL SIZE :   | 11                       |   |   |    |   | CONTACT LAYOUT : 11-04          |   |   |   |                        |
| PLATING :      | J = Olive drab Cadmium   |   |   |    |   |                                 |   |   |   |                        |

Contact Layout



| Contacts<br>(Insert arrangement 11-4) |                  |              |
|---------------------------------------|------------------|--------------|
| Contact position ID                   | Contact location |              |
|                                       | X-axis (mm)      | Y-axis (mm)  |
| A                                     | +0.65 (1.65)     | +0.65 (1.65) |
| B                                     | +0.65 (1.65)     | -0.65 (1.65) |
| C                                     | -0.65 (1.65)     | -0.65 (1.65) |
| D                                     | -0.65 (1.65)     | +0.65 (1.65) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 11         | -4              | 4                  | 20            | I              | All              | MS20050-4  |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 20.22 min  |
| ØAA | 15.88 min  |
| R1  | 20.62      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D011J04PDL

|                |                                       |                            |   |
|----------------|---------------------------------------|----------------------------|---|
| A              | 06-10-2016                            | First Release              |   |
| ISS            | DATE                                  | Latest modification - by   | MOD N°  |
| Designed By:   |                                       | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Composite Receptacle 8D series</b> |                            |   |
| SCALE          |                                       | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                       | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D011J04PDL-C</b>   |                            | SHEET 2/2   |