



# **SUMMARY**

#### # Wires

Low voltage 16



Image is for illustrative purpose only

Series 2P

Termination type Female solder

IP rating 50

AWG wire size 30.00 - 22.00

Cable Ø 3.20 - 9.20 mm

**Status** active

Matching parts CAB.M16.GLA.C52G

#### **Download**

Request a quote

Catalog

# **TECHNICAL DETAILS**

#### Mechanics

Shell Style/Model CK\*: Fixed receptacle with two nuts (back panel mounting)

Keying 3 keys (alpha=0, gamma=60; Plug: male contacts; Receptacle: female contacts)

Housing Material PSU (Polysulfone), gray

Weight 6.55 g

### **Performance**

Configuration 2P.M16: 16 Low V.

Insulator L: PEEK for solder contacts

Rated Current 6 Amps

## **Specifications**

Contact Type: Solder

Contact Dia.: 0.7 mm (0.027in) Bucket Dia.: 0.8 mm (0.031in)

Test voltage (kV rms) Contact-contact: 1.5

Air clerance min.: 0.47 mm Creepage distance min.: 0.47 mm

#### **Others**


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Endurance (Shell): >1000 mating cycles

F ret (min): 150 N F ret (max): 250 N

Steam sterilization: 20 times

# **DRAWINGS**







## **Dimensions**

		А	N	a
	mm.	20.2	23.8	3.4-4.9
	in.	0,80	0,94	0,13

# **RECOMMENDED BY LEMO**

#### **Tools**

### **Cables**

CMN.16.B22.084PG3Z		Grey	
CMN.16.T22.076QGZE	TPR (medical)	Grey	>
CMN.16.T28.059PGZE		Grey	>
CMN.16.T28.059PNZE			

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

CMN.16.T28.070NNZZ			
CMN.16.T30.047QGZE	TPR (medical)	Grey	
116080	PUR	Black	
116280	PVC	Black	
16050	PVC	Black	
216220	PVC	Black	
216240	PVC	Black	
216260	PVC	Black	
316250	PVC	Grey	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.