



Click [here](#) for the 3D model.

### Dimensions

|           |                    |
|-----------|--------------------|
| L         | 280mm NOM          |
| W         | 140mm NOM          |
| H         | 170mm NOM          |
| L1        | 230mm NOM          |
| W1        | 153.5mm NOM        |
| W2        | 170mm NOM          |
| J         | 50mm NOM           |
| K         | 6.5mm NOM          |
| M (Earth) | Threaded Studs M10 |

### Packaging Specifications

|                    |        |
|--------------------|--------|
| Packaging          | Bulk   |
| Packaging Quantity | 1      |
| Component Weight   | 6100 g |

### General Information

|                |                                    |
|----------------|------------------------------------|
| Series         | FLLD4-TH                           |
| Style          | Chassis Mount                      |
| Description    | EMI Filter, Chassis Mount, Compact |
| Features       | High Performance                   |
| Phase          | Three-phase + Neutral              |
| RoHS           | Yes                                |
| Qualifications | IEC/EN 60939                       |
| Terminal Type  | Terminal Block                     |

### Specifications

|                          |                   |
|--------------------------|-------------------|
| Voltage AC               | 530 VAC           |
| Rated Frequency          | 50-60 Hz          |
| Rated Current            | 200 A (50°C)      |
| Rated Temperature        | 50°C              |
| Temperature Range        | -25/+100°C        |
| Climate Category         | 25/100/21         |
| Test Voltage DC (P to P) | 2250 VDC          |
| Test Voltage DC (P to E) | 3000 VDC          |
| Power Loss               | 45 W (25°C 50 Hz) |
| Leakage Current          | 11 mA             |