

Tripp Lite
1111 W. 35th Street

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

7-Port USB 2.0 Hub

MODEL NUMBER: U222-007-R











Description

Tripp Lite's ultra small 7-port USB 2.0 hub is the most versatile and powerful hub on the market. It allows you to connect up to seven USB devices to a single USB port on your computer. This unit meets or exceeds USB 2.0 Specifications for Hi-Speed data transmission rates up to 480Mbps. Perfect for both the mobile and desktop user. While the hub will function perfectly in virtually all cases without needing external power, a compact, multi-voltage AC adapter (100-240V) has been provided for the rare circumstance when connecting a power hungry device. This USB 2.0 device is backwards compatible so that it will function with both USB 2.0 and USB 1.1 devices. Over-current protection safeguards connected equipment from overvoltages. Includes stand for upright positioning.

Features

- USB2.0 7-Port Hub
- Supports data transfer rates up to 480Mbps
- Connect up to 7 USB devices to a single USB port on your computer
- Compact design is ideal for use with a laptop/notebook computer
- Does not require external power, software, or complicated set-up procedures
- Plug-and-play/hot-swappable allows you to add or remove a device at any time
- Per-port overcurrent protection
- Bus-powered or self-powered
- Supports USB 2.0 spec up to 500mA per port
- On bus-power, 500mA from the USB 2.0 computer port is shared between the hub ports
- The included external power supply provides 2.5A of power, to be shared between the hub ports (up to 500mA per port)
- Compact, multi-voltage power supply (100-240V) provided
- · Compatible with all major operating systems

Highlights

- Connect up to 7 USB 2.0 devices
- Hi-Speed 480Mbps data transfer
- Backward compatible with USB
 1.1 devices
- Over-current protection safeguards connected equipment from overvoltages
- Supports USB 2.0 spec up to 500mA per port
- Includes base stand for upright positioning
- Compatible with all major operating systems

System Requirements

- USB 2.0 port
- Compatible with all major operating systems

Package Includes

- U222-007-R USB 2.0 7-Port
 Mini Hub
- Compact External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A;
 Output: 5V, 2.5A)
- 4 ft. extension cable



Specifications

INPUT Voltage Compatibility (VAC) 100; 110; 120; 127; 200; 208; 220; 230; 240			
No	OVERVIEW		
Voltage Compatibility (VAC) 100; 110; 120; 127; 200; 208; 220; 230; 240 External Power Supply Input Specs (V / Faz / A) 100-240V / 50/60Hz / 0.5A External Power Supply Output Specs (V / A) 5V / 2.5A Specs (V / A) 5V / 2.5A External Power Supply Cord Length (ft) 5 External Power Supply DC Barrel Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sieeve External Power Supply Plug(s) NEMA 1-15P North America External Power Supply Certifications FCC; UL; cUL; ROHS Bus Powered No USER INTERFACE, ALERTS & CONTROLS LED Indicators Red (Power) PHYSICAL Shipping Dimensions (hwd / in.) 8.90 x 5.60 x 2.50 Shipping Weight (kg) 0.45 Unit Packaging Type Clamshell Unit Unity Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C)<	UPC Code	037332126733	
External Power Supply Input Specs	INPUT		
External Power Supply Output 55	Voltage Compatibility (VAC)	100; 110; 120; 127; 200; 208; 220; 230; 240	
Specs (V/ A) SOFT ALLOW External Power Supply Cord Length (t) 5 External Power Supply PC Barrel Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve External Power Supply Plug(s) NEMA 1-15P North America External Power Supply Certifications FCC; UL; cUL; RoHS Bus Powered No USER INTERFACE, ALERTS & CONTROLS LED Indicators Red (Power) PHYSICAL Shipping Dimensions (hwd / in.) 8.90 x 5.60 x 2.50 Shipping Weight (kg) 0.45 Unit Packaging Type Clamshell Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.5A	
External Power Supply DC Barrel Connector Specs External Power Supply Plug(s) NEMA 1-15P North America External Power Supply Certifications FCC; UL; cUL; RoHS Bus Powered No USER INTERFACE, ALERTS & CONTROLS LED Indicators Red (Power) PHYSICAL Shipping Dimensions (hwd / in.) 8.90 x 5.60 x 2.50 Shipping Weight (kg) 0.45 Unit Packaging Type Clamshell Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	External Power Supply Output Specs (V / A)	5V / 2.5A	
External Power Supply Plug(s) External Power Supply Plug(s) External Power Supply Certifications FCC; UL; cUL; RoHS Bus Powered No USER INTERFACE, ALERTS & CONTROLS LED Indicators Red (Power) PHYSICAL Shipping Dimensions (hwd / in.) Shipping Weight (kg) Unit Packaging Type Clamshell Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	External Power Supply Cord Length (ft.)	5	
External Power Supply Certifications FCC; UL; cUL; RoHS	External Power Supply DC Barrel Connector Specs	OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve	
Bus Powered No	External Power Supply Plug(s)	NEMA 1-15P North America	
USER INTERFACE, ALERTS & CONTROLS LED Indicators Red (Power) PHYSICAL Shipping Dimensions (hwd / in.) 8.90 x 5.60 x 2.50 Shipping Weight (kg) 0.45 Unit Packaging Type Clamshell Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	External Power Supply Certifications	FCC; UL; cUL; RoHS	
Red (Power)	Bus Powered	No	
PHYSICAL Shipping Dimensions (hwd / in.) 8.90 x 5.60 x 2.50 Shipping Weight (kg) 0.45 Unit Packaging Type Clamshell Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	USER INTERFACE, ALERTS & CONTROLS		
Shipping Dimensions (hwd / in.) Shipping Weight (kg) 0.45 Unit Packaging Type Clamshell Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	LED Indicators	Red (Power)	
Shipping Weight (kg) 0.45 Unit Packaging Type Clamshell Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	PHYSICAL		
Unit Packaging Type Clamshell Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity O% to 90 RH, Non-Condensing	Shipping Dimensions (hwd / in.)	8.90 x 5.60 x 2.50	
Unit Dimensions (hwd / in.) 0.94 x 3.4 x 2.7 Unit Weight (lbs.) 0.2 Unit Weight (kg) 0.09 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	Shipping Weight (kg)	0.45	
Unit Weight (lbs.) Unit Weight (kg) O.9 Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity O% to 90 RH, Non-Condensing	Unit Packaging Type	Clamshell	
Unit Weight (kg) Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	Unit Dimensions (hwd / in.)	0.94 x 3.4 x 2.7	
Material of Construction ABS Color Black; White ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	Unit Weight (lbs.)	0.2	
ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	Unit Weight (kg)	0.09	
ENVIRONMENTAL Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	Material of Construction	ABS	
Operating Temperature Range 32 to 104 F (0 to 40 C) Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	Color	Black; White	
Storage Temperature Range 14 to 176 F (-10 to 80 C) Relative Humidity 0% to 90 RH, Non-Condensing	ENVIRONMENTAL		
Relative Humidity 0% to 90 RH, Non-Condensing	Operating Temperature Range	32 to 104 F (0 to 40 C)	
	Storage Temperature Range	14 to 176 F (-10 to 80 C)	
BTUs 8.5 BTU/Hr	Relative Humidity	0% to 90 RH, Non-Condensing	
	BTUs	8.5 BTU/Hr	





CONNECTIONS		
Ports	7	
Side A - Connector 1	USB B (FEMALE)	
Side B - Connector 1	(7) USB A (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
USB Specification	USB 2.0 (up to 480 Mbps)	
Driver Required	No	
Technology	USB 2.0 (High Speed); USB	
CERTIFICATIONS		
Approvals	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies