



All dimensions are in mm; tolerances acc. to ISO 2768 m-H

**Interface**

RPC-2.92 according to  
RPC-2.92 mechanically compatible with  
SMP according to

IEC 61169-35  
RPC-3.50 and SMA  
MIL-STD-348A, Fig. 326

**Documents**

N/A

**Material and plating**

**Connector parts**

- Center contact
- Outer contact RPC-2.92
- Outer contact SMP
- Coupling nut
- Dielectric
- Gasket

**Material**

- CuBe
- Stainless steel
- CuBe
- Stainless steel
- PEEK
- Silicone

**Plating**

- Gold, min. 1.27 µm, over chemical nickel
- Passivated
- AuroDur®, gold plated
- Passivated

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/06.13/6.1

Adaptor  
RPC-2.92 Plug – SMP Plug limited detent

**02S119-S00E3**

**Electrical data**

Frequency range	DC to 40 GHz
Return loss	≥ 32 dB, DC to 12 GHz
	≥ 26 dB, 12 GHz to 26.5 GHz
	≥ 21 dB, 26.5 GHz to 40 GHz

**Mechanical data**

Mating cycles RPC-2.92	≥ 500
Mating cycles SMP (limited detent)	≥ 500
Center contact captivation RPC-2.92	≥ 20 N
Center contact captivation SMP	≥ 7 N
Engagement force SMP (limited detent)	≤ 45 N
Disengagement force SMP (limited detent)	≥ 9 N
Recommended torque RPC-2.92	0.80 Nm to 1.10 Nm
Gauge RPC-2.92	0.00 mm to 0.08 mm
Gauge SMP	0.00 mm to 0.05 mm

**Environmental data**

Operating temperature range <sup>1</sup>	+20 °C to +26 °C
Storage temperature range	0 °C to +50 °C
RoHS	compliant

<sup>1</sup> Temperature range over which these specifications are valid.

**Packing**

Standard	1 pce in box
Weight	10.9 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Herbert Babinger	06.12.04	O. Krautenbacher	12.11.13	e00	13-1287	Manuela Fuehrich	12.11.13
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>				Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>			Page 2 / 2