











5.80

10.70

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED	4V-0
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	75Ω (IMPEDANCE)	
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	J
WITHSTANDING VOLTAGE:	1000V AC rms	

S		
	SW REFERENCE NO .:	630 COMBO A



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



ARIO OR USED AS THE BASIS FOR THE MANUFACTURE OF ADAC INC. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

COMBINATION D-SUB

0 COMBO ASSEMBLY
DATE: JAN. 01/2019
DATE:
SHEET 1 OF 2
V2-640-7N2 ISSUE
V2-640-7N2 1

