Mounting Option .468 (11.89) Offset Card Guides **Contact Detail** Wire Hole .087x.013(2.21x0.33) - Tail LG=.282(7.16) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing 3.586 [91.08] 3.440 [87.38] 0.343[8.71] 0.473 [12.01]



.175 [4.45] Point of Contact (Measured from bottom of Card Slot) Card Slot Accepts .054 [1.37] to .070 [1.78] Thick P.C. Board **SECTION A-A**

See Accompanying Pages for:

- **Contact Bend Details**
- **Mounting Options**
- **Features and Specifications**

807 Series High Temp Card Edge Connector Part Number: 807-021-505-158



| | DRAWN: J.LEE | DATE: AUG. 11/09 | | | |
|---|----------------|------------------|--|--|--|
| | CHECKED: | DATE: | | | |
| | SCALE: NTS | SHEET 1 OF 4 | | | |
| D | DRAWING NUMBER | ISSUE | | | |
| | | | | | |

ACAD REFERENCE NO.

807 Assembly

807 ENG MASTER





ISSUE NUMBE

ORIGINAL



Features

- CSA Approved and UL Recognized
- .156 (3.96) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- Low Profile Insulator Body .473 (12.01), with Card Guides
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree & Extender Board Bends
- Single or Dual Row Configurations
- Large Variety of Mounting Options
- Pre-assembled Card Guides Available
- Accepts Between Contact and In-Contact Polarizing Keys

Specifications

- Insulator Material: DAP
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 5 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1800 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Resistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +165 °C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

| 807 Series High Temp Card I | ACAD REFERENCE NO. 807 ENG MASTER | | | | |
|-----------------------------|---|---------|-------------|----------|----------|
| Features and Specifications | | | J.LEE | DATE: AU | G. 11/09 |
| reatures and specifications | | CHECKE |): | DATE: | |
| EDAC INC | THESE DRAWINGS AND SPECIFICATIONS | SCALE: | NTS | SHEET . | 4 OF 4 |
| CANADA | ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | DRAWING | NUMBER | | ISSUE |
| | | 8 | 07 Assembly | | 1 |