




Item	Date	Remark
A	20071112	Original Drawing
B	20071122	Shrink Panel Size
C	20071126	Modify Active Area Position



Pin	Symbol
1	N.C. (GND)
2	VLSS
3	VSS
4	N.C.
5	VDD
6	BS1
7	BS2
8	CS#
9	RES#
10	D/C#
11	R/W#
12	E/RD#
13	D0
14	D1
15	D2
16	D3
17	D4
18	D5
19	D6
20	D7
21	IREF
22	VCOMH
23	VCC
24	N.C. (GND)

- Notes:
- Color: Light Blue
 - Driver IC: SSD1305
 - FPC Number: UT-0205-P05
 - Interface:
8-bit 68XX/80XX Parallel, 4-wire SPI, I2C
 - General Tolerance: ±0.30
 - The total thickness (2.10 Max) is without polarizer protective film & remove tape.
The actual assembled total thickness with above materials should be 2.35 Max.

Customer Approval Signature	Univision Technology Inc.							Drawing Number	Rev.	
		UG-2832ALBCG01 Folding Type OEL Display Module Pixel Number: 128 x 32, Monochrome, COG Package							DMX2832CNGF13	C
	Material							Soda Lime / Polyimide		
	Title		Drawn	E.E.	Panel / E.	P.M.	Scale	Sheet	Size	
	Dimension		Humphrey Lin	James Wang	Ivy Lo	Sean Lin	1:1	1 of 1	A3	
	Angle		Date	20071126	20071126	20071126	20071126			