

## **Specification Sheet**

Part Number: 596-00867

Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.

Aggressive adhesive ensures strong bond, even on powder coated surfaces.

Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.



Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Metal Solar Placard, Blank Plate For Engraving, 4.0" x .75", AA, Black, 5/pkg

Article Number 596-00867

Type BLANK4X75

Color Black (BK)

Quantity Per pack

**Product Description** Variable data placards are used to mark areas specific to the

individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, engravable placards are designed to meet industry codes. Engravable placards have a black area that can be engraved using standard engraving equipment.

**Short Description** Metal Solar Placard, Blank Plate For Engraving, 4.0" x .75", AA, Black, 5/pkg **Global Part Name** BLANK4X75-AA-BK **Technical Description** 4.0" X 0.75" Black surface for engraving custom metal placards - 5 per pack. 4.0 Width W (Imperial) Width W (Metric) 101.6 Height H (Imperial) .75 19.05 **Height H (Metric)** Material Anodized Aluminum (AA) **Material Shortcut** AA Adhesive Ultra High Bond Permanent Acrylic Adhesive **Halogen Free** No

from +50°F (from +10°C)

Operating Temperature -40°F to +203°F (-40°C to +95°C)

Reach Compliant (Article 33) Yes

**Adhesive Operating Temperature** 

ROHS Compliant	Yes
Certification/Specification	NEC2014 NEC2017
Warranty (US)	Yes
Package Quantity (Imperial)	5
Package Quantity (Metric)	5
Customs Number	3919905060
Labels per Column	1
Labels per Row	1

© 2021 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions