	m m		0			
			LAYOUT SHOWN AS EXA	MPLE		
	Keying Shown as example					
CHARACTERISTICS						
-Standard : Based on MIL-DTL-38999 Series III	Connector dimensionDimNominalØS25 Max					
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List		
 -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles 			FR	Not Listed		
-Delivered with Souriau contacts and Accessories			PN: 8D511F01SD			
-Temperature Range : -65°C to +200°C		A 15-10-2016	First Palazsa			
-Salt Spray : 48 hours						
Mass : 17.92 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
TITLE Aluminium Plug 8D s				m Plug 8D series		
BASIC SERIES: 8D 5 - 11 F 01	S D	SCALE	General linear	NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding		NA -	Tolerances:	859		
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : D	_		This document is the pr SOURIAU	operty of	
SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matir		- SUUKIAU	WWW.SOURIAU.COM it must not be reproduced or communicated without permission			
PLATING : F = Nickel	CONTACT THE SOCKET (SOU WAITINGS	-	SOURIAU D		SHEET	
		- A3	8D511F01		1/2	
					-/-	

	т	۵	нт — — — — — — — — — — — — — — — — — — —	т	U	0
		Contact Layout				
4		01				
		1#12 11-01	٦			
ω	Ctc A	X Y 0 0				
	-					SOURIAU shall not be liable for any due to a use of the Products wh
N						the Specifications issued by either of (professional recommendat Countr FR
					A 15-10-20 ISS DATE Designed By:	PN: 8D5111
_					TITLE SCALE NA	Alumin General linear Tolerances: ±
					FORMAT A3	J WWW.SOURIAU.C SOURIAU 8D511F0
l	Н	G	F	E	D	C C

