| ⊥ <u></u> | П | m | | 0 | | | |
|--|-----------------|--|--|---|---------------------------------|--|--------------|
| | ØS | | | | | | |
| | | | | LAYOUT SH | HOWN AS EXAMPLE | | |
| | Keying Shown as | example | | | | | |
| CHARACTERISTICS | F | Connector dimension Dim Nominal | | | | | |
| -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer | | ØS 29.4 Max Z' 31.5 Max VV THREAD M18x1-6g | | SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) | | | |
| -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles | | | | | FR | Not Listed | |
| -Delivered with Souriau contacts and Accessories -Temperature Range <u>-</u> -65°C to +175°C | | | | PIN: 8 | 8D513J98PD | | |
| -Salt Spray : 2000 hours -Mass : 17.2 g ± 10% | | | A 17-10-2016 ISS DATE Designed By: | First Release Latest modification - by Date: | | CUSTOMER DRAWING | MOD N° |
| | | | TITLE | | Composite Plug 8 | D series | |
| BASIC SERIES: 8D 5 - 13 . SHELL TYPE : Plug with RFI Shielding | J 98 P D | | SCALE -[- | | neral linear olerances: ± | NPRDS / PROJECT 859 | |
| CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13 | | ORIENTATION : D CONTACT TYPE : PIN(500 Matings) | - SUUKIAU | WWW.SOU | JRIAU.COM | This document is the prope SOURIAU it must not be reproduce communicated without perr | d or |
| PLATING : J = Olive drab Cadmium | | CONTACT LAYOUT : 13-98 | - | | URIAU DRG N° D513J98PD-C | | SHEET 1/2 |
| | | | | 01 | D-0-0-0-C | | , = |

| - | Ŧ | ۵ | н г | m | D | 0 |
|----------|--|--|------------|---|--------------|---|
| | | Contact Layout | | | | |
| 4 | | $ \begin{array}{c} \bullet \\ & \bullet \\ $ | | | | |
| | Con positiv A E C C C C C C C C C C C C C C C C C C | $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$ | | | | |
| ω | Shell Arrangement No. c | Number Size Service Contact Supersedes of contacts rating location 10 20 I All MS20051-96 | | | | |
| | l | | | | | |
| | | | | | | SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda |
| N | | | | | | Count FR |
| | | | | | | PN: 8D513 |
| | | | | | A 17-10-20 | 016 First Release |
| _ | | | | | ISS DATE | Latest modification - by Date: |
| | | | | | Designed By: | Comp |
| <u> </u> | | | | | SCALE | General linear Tolerances: |
| | | | | | SOURIA | U WWW.SOURIAU. |
| | | | | | FORMAT A3 | SOURIAU 8D513J |
| L | Н | G | F | E | D | C |

