



GTX-2060-Y22

Aliases (UNFGX2060Y22XX)

KEMET, GTX, EMI/RFI Filters, Noise Suppression, 250 VAC, 560 VDC, 6 A, 75x44x25mm







Click here for the 3D model.

Dimensions	
L	75mm +/-1mm
W	44mm +/-1mm
Н	25mm +/-1mm
S	17.6mm NOM
L1	66.7mm +/-0.5mm
W1	35mm +/-0.5mm

Packaging Specifications		
Packaging Quantity	30	
Component Weight	125 g	

General Information		
Series	GTX	
Style	Plastic Box	
Description	EMI Filter, With Y Capacitor	
Phase	Single-phase	
RoHS	With Exemptions	
Qualifications	UL, cUL, TUV	
Tightening Torque	1.2 ~ 1.4N-m (Recommended)	
Line Terminal	14-4(JST)	
Line Terminal Width	12 Max.	
Earth Terminal	R5.5-4(JST)	
Earth Terminal Width	9.5 Max.	
Miscellaneous	60 K Self-Temperature Rise Max.	
Terminal Type	Screw	

Specifications	
Voltage AC	250 VAC
Voltage DC	560 VDC
Rated Current	6 A
Temperature Range	-25/+55°C
Leakage Current	1 mA (MAX)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.