

Half screw connection - VC-M-KV-PG16(11,5-15,5) - 1854857

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Half screw connection Pg16, made of metal, consisting of rubber seal with one hole and one pressure screw, for type 1 housings, cable [mm] 11.5 - 15.5



Key Commercial Data

Packing unit	5 pc	
GTIN	4 017918 146047	
GTIN	4017918146047	

Technical data

Dimensions

Length	24.7 mm
Wrench size, union nut	24 mm
External cable diameter	11.5 mm 15.5 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C 125 °C

General

Note	Adapter screw connections are available on request for large cable dimensions, from Pg16 to Pg21 and from Pg21 to Pg29	
No. of conductors	1	
Material, pressure screw	Nickel-plated brass	
Seal material	TPE	
Cable seal material	TPE	
Sealing material	TPE	
Shielded	no	
Thread type on seal side	Pg16	
Tightening torque, union nut	7.50 Nm	



Half screw connection - VC-M-KV-PG16(11,5-15,5) - 1854857

Technical data

Environmental Product Compliance

	Lead 7439-92-1		
China RoHS	Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"		

Approvals

Approvals

Approvals		
EAC		
Ex Approvals		

Approval details

EAC

B.01742

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

EHE

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com