
TOLERANCE
 THIS IS A C.A.D. GENERATED DRAWING


 UNLESS OTHERWISE SPECIFIED
 DO NOT MAKE MANUAL REVISIONS TO MASTER.


 .X
 ±0.25











NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

OPERATING TEMPERATURE:

.XX ±0.13 .XXX ±0.05

POWER/CO-AX CONTACT RATING:10A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.


1000V AC rms

STEEL, TIN PLATED

-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, GOLD FLASH PLATED



| | COMBINATION D-SUB | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | |
|---|----------------------------|--|--------------------------------------|-------------------|-------|
| | | | DRAWN: C.B | DATE: JAN. 01/201 | 19 |
| | | | CHECKED: | DATE: | |
| | EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 |
| | TORONTO, ONTARIO CANADA | | DRAWING NUMBER: 629-7W2-240-1TD | | ISSUE |
| Y | | | PART NUMBER: 629-7W2- | 240-1TD | 1 |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

