## ATGBICS DWDM-SFP10G-48.51 Cisco Compatible Transceiver DWDM SFP+ 10GBase (1480.51nm, SMF, 40km, DOM)

Brand : ATGBICS

Product code: DWDM-SFP10G-48.51-C




**Product name :** DWDM-SFP10G-48.51 Cisco Compatible Transceiver DWDM SFP+ 10GBase (1480.51nm, SMF, 40km, DOM)

DWDM-SFP10G-48.51 Cisco Compatible Transceiver DWDM SFP+ 10GBase (1480.51nm, SMF, 40km, DOM)

ATGBICS DWDM-SFP10G-48.51 Cisco Compatible Transceiver DWDM SFP+ 10GBase (1480.51nm, SMF, 40km, DOM):

ATGBICS DWDM-SFP10G-48.51 10GBase DWDM supports a distance of up to 40km over single mode fibre (SMF) using a wavelength of 1480.51nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of CiscoDWDM-SFP10G-48.51= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

Performance		Power	
Maximum data transfer rate *1Interface type *SSingle-mode fiber (SMF) supportedImage: Single-mode fiber (SMF) supportedMulti-mode fiber (MMF) supportedImage: Single-mode fiber (SMF) supportedFiber optic connectorImage: Single-mode fiber (SMF) supportedSFP transceiver standardImage: Single-mode fiber (SMF) supportedMaximum transfer distanceImage: Single-mode fiber (SMF) supportedWavelength1Ethernet LANImage: Single-mode fiber (SMF) supported		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
		Weight & dimensions	
Digital Diagnostics Monitoring (DDM)		Width Depth	13.4 mm 56.5 mm
Features		Height	8.5 mm
Product colour	Silver	Weight	19 g
Housing material	Metal	Packaging data	
lug and Play ot-swap	4	Number of products included Package type	1 pc(s) Box
Easy to install Country of origin	United Kingdom Cisco CE, FCC, RoHS	Technical details	
Brand compatibility Certification		Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468715319

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.