


Specifications			Notes	Revision History															
Description	Value	Unit		Version	Description	Date	Approved												
Resonant Frequency	1,000	(Hz)	1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS	1	Released from Engineering	10/21/2013	J.S												
Resonant Impedance (Max)	300	(Ohm)																	
Max Input Voltage	30	(V)																	
Capacitance	65,000	(pF)																	
Plate Material	Brass																		
Operating Temperature	-20 ~ +60	°C																	
Storage Temperature	-20 ~ +70	°C																	
			 DB UNLIMITED	Piezo Bender	P41010-1														
			<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Drawn by</th> <th style="text-align: left;">Date</th> <th style="text-align: left;">Checked by</th> <th style="text-align: left;">Date</th> <th style="text-align: left;">Approved by</th> <th style="text-align: left;">Date</th> </tr> </thead> <tbody> <tr> <td>A.B.</td> <td>10/21/2013</td> <td>C.E.</td> <td>10/21/2013</td> <td>J.S</td> <td>10/21/2013</td> </tr> </tbody> </table>		Drawn by	Date	Checked by	Date	Approved by	Date	A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013			
Drawn by	Date	Checked by	Date	Approved by	Date														
A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013														

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.