



AEC-Q200


This component was always RoHS compliant from the first date of manufacture.

- **Designed for European 433.92 MHz Remote Control and Security Transmitters**
- **Very Low Series Resistance**
- **Quartz Stability**
- **Complies with Directive 2002/95/EC (RoHS)**
- **Tape and Reel Standard per ANSI/EIA-481**
- **Passivation for enhanced reliability**



RO3101E-20

**433.92 MHz
SAW
Resonator**



The RO3101E-20 is a true one-port, surface acoustic wave (SAW) resonator in a surface mount ceramic case. It provides reliable, fundamental mode, quartz frequency stabilization of fixed frequency transmitters operating at 433.92 MHz. This SAW is designed specifically for remote control and wireless security transmitters operating in Europe ETSI I-ETS 300 200 regulations.

Absolute Maximum Ratings

Rating	Value	Units
Input Power Level	0	dBm
DC voltage	12	VDC
Storage Temperature Range	-40 to +125	°C
Operating Temperature Range	-40 to +105	°C
Soldering Temperature (10 seconds / 5 cycles maximum)	260	°C

Electrical Characteristics

Characteristic		Sym	Notes	Minimum	Typical	Maximum	Units	
Center Frequency, +25 °C	Absolute Frequency	f_C		433.845		433.995	MHz	
	Tolerance from 433.920 MHz	Δf_C				±75	kHz	
Insertion Loss		IL			1.4	2.2	dB	
Quality Factor	Unloaded Q	Q_U			8280			
	50 Ω Loaded Q	Q_L			1228			
Temperature Stability	Turnover Temperature	T_O		10	25	35	°C	
	Turnover Frequency	f_O			f_C			
	Frequency Temperature Coefficient	FTC			0.032		ppm/°C ²	
Frequency Aging	Absolute Value during the First Year	$ f_A $			≤10		ppm/yr	
DC Insulation Resistance between Any Two Terminals				1.0			MΩ	
RF Equivalent RLC Model	Motional Resistance	R_M			17.5		Ω	
	Motional Inductance	L_M			53.5		μH	
	Motional Capacitance	C_M			2.5		fF	
	Shunt Static Capacitance	C_O			2.5		pF	
Test Fixture Shunt Inductance		L_{TEST}			53.2		nH	
Lid Symbolization (in addition to Lot and/or Date Codes)	779, YWWS							
Standard Reel Quantity	Reel Size 7 Inch						500 Pieces/Reel	
	Reel Size 13 Inch						3000 Pieces/Reel	

CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.


NOTES:

1. The design, manufacturing process, and specifications of this device are subject to change.
2. US or International patents may apply.
3. RoHS compliant from the first date of manufacture.

Electrical Connections

The SAW resonator is bidirectional and may be installed with either orientation. The two terminals are interchangeable and unnumbered. The callout NC indicates no internal connection. The NC pads assist with mechanical positioning and stability. External grounding of the NC pads is recommended to help reduce parasitic capacitance in the circuit.


Pin	Connection
1	NC
2	Terminal
3	NC
4	NC
5	Terminal
6	NC



Case and Typical PCB Land Dimensions


Ref	mm			Inches		
	Min	Nom	Max	Min	Nom	Max
A	2.87	3.00	3.13	0.113	0.118	0.123
B	2.87	3.00	3.13	0.113	0.118	0.123
C	1.12	1.25	1.38	0.044	0.049	0.054
D	0.77	0.90	1.03	0.030	0.035	0.040
E	2.67	2.80	2.93	0.105	0.110	0.115
F	1.47	1.60	1.73	0.058	0.063	0.068
G	0.72	0.85	0.98	0.028	0.033	0.038
H	1.37	1.50	1.63	0.054	0.059	0.064
I	0.47	0.60	0.73	0.019	0.024	0.029
J	1.17	1.30	1.43	0.046	0.051	0.056
K		3.20			0.126	
L		1.70			0.067	
M		1.05			0.041	
N		0.81			0.032	
O		0.38			0.015	

Equivalent RLC Model




Temperature Characteristics

The curve shown accounts for resonator contribution only and does not include external LC component temperature effects.




Characterization Test Circuit

Inductor L_{TEST} is tuned to resonate with the static capacitance, C_0 , at F_c .




Power Dissipation Test




Example Application Circuits

Typical Low-Power Transmitter Application



Typical Local Oscillator Application



Recommended Reflow Profile

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (10 seconds).
4. Time: 5 times maximum.

