Mo In-	Dunting Option Line Card Guides	Contact Detail Wire Hole .089x.014(2.29x0.36) - Tail LG=.213(5.41) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing	THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MAST	ER.	ISSUE NUMBER ORIGINAL 1
0.500[12.70]	0.156[3.96]	6.248[158.70] ————————————————————————————————————		SECTI	ION A-A
	A				
			<u> </u>		
=				.175 [4.45] Point of Contact (FROM BTM OF SLOT)	
0.473 [12.01]	6.990[177.55] — Card S to .070			d Slot Accepts .054 [1.37] 170 [1.78] Thick P.C. Board	
	See Accompanying Pages for: Contact Bend Details	307 / 357 Card Ed	dge Connector	ACAD REFERENCE NO.	307 ENG MASTER
		Part Number: 357	_	DRAWN: J.LEE CHECKED:	DATE: AUG. 11/09 DATE:
			EDAC INC THESE DRAWINGS AND SPECIFICATIONS	SCALE: NTS	SHEET 1 OF 3
	 Mounting Options 		ONTO, ONTARIO ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED	DRAWING NUMBER	ISSUE
		YOUR CONNECTION TO QUAL	YOUR CONNECTION TO QUALITY & SERVICE OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATU MITHOUT WRITTEN PERMISSION.		1



