## SIEMENS

## Data sheet

## 3SU1000-0AA10-0AA0-Z Y11



Pushbutton, 22 mm, round, plastic, black, pushbutton, flat, latching, Pushto-release mechanism, with laser labeling, upper case

product brand name	SIRIUS ACT		
product designation	Pushbuttons		
design of the product	Actuating/signaling element		
product type designation	3SU1		
product line	Plastic, black, 22 mm		
Enclosure			
number of command points	1		
Actuator			
design of the actuating element	Flat button		
principle of operation of the actuating element	latching		
product extension optional			
light source	No		
contact module	Yes		
color of the actuating element	black		
material of the actuating element	plastic		
shape of the actuating element	round		
outer diameter of the actuating element	29.5 mm		
marking of the actuating element	Any inscription, text in upper case		
type of unlocking device	push-to-unlatch mechanism		
Front ring			
product component front ring	Yes		
design of the front ring	Standard		
material of the front ring	plastic		
color of the front ring	black		
General technical data			
protection class IP	IP66, IP67, IP69(IP69K)		
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13		
shock resistance			
• acc. to IEC 60068-2-27	Sinusoidal half-wave 50g / 11 ms		
<ul> <li>for railway applications acc. to DIN EN 61373</li> </ul>	Category 1, Class B		
vibration resistance			
• acc. to IEC 60068-2-6	10 500 Hz: 5g		
<ul> <li>for railway applications acc. to DIN EN 61373</li> </ul>	Category 1, Class B		
	1 800 1/h		
operating frequency maximum	1000 1/11		
operating frequency maximum mechanical service life (switching cycles) typical	500 000		

## ambient temperature during operation

ambient temperature during storage

-25 ... +70 °C -40 ... +80 °C

environmental category during operation acc. to IEC

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %)

607	21	

Installation/ mounting/ dimensions		
height	29.5 mm	
width	29.5 mm	
shape of the installation opening	round	
mounting diameter	22.3 mm	
positive tolerance of installation diameter	0.4 mm	
mounting height	11 mm	
installation width	29.5 mm	
installation depth	24.3 mm	
Certificates/ approvals		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-0AA10-0AA0-Z Y11

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1000-0AA10-0AA0-Z Y11

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-0AA10-0AA0-Z Y11

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <u>http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1000-0AA10-0AA0-Z Y11&lang=en</u>

last modified:

1/5/2021 🖸