© Cor	erial Compositi byright 2005. IPC, B ational and Pan-Am	annockbu	urn, Illinois. A	ll rights reserved nations.	under both	This docume level parts, t	ent is a declara he declaration	tion of the s encompasse	ubstances v s all lower	within the manufact level materials for	urer listed which the	item. Note: manufacture	if the item is an as er has engineering	sembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information				
upplier Information															
Company name*			Company unique ID				Unique ID Authority				Respor	Response Date*			
onsemi											2023-0	2023-06-08			
Contact Name T			Title - Contact				Phone - Contact*				Email	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative				Phone - Representative*				Email	Email - Representative*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item N	Requester Item Number Mfr Iten		m Number Mfr Item Name				Effective Date Version		N	Manufacturing Site		Weight*	UOM	Unit Type	
	1	MC74VHC257DG LOG CMOS		LOG CMOS QU	OS QUAD MLTIPLXR		2023-06-08		P	PH1		142.69	mg	Each	
Ianufacturing Procee	ss Information							-							
Terminal Plating / Grid Array Material Terminal Base		Alloy	loy J-STD-020 MSL Rating			Peak Process Body Temperature Max Time at Peak			ık Tempera	Temperature Number of Reflow Cycles					
Matte Tin (Sn) - annealed CU		U Alloy	y <u>1</u>			260	C 30		30	seconds 3					
omments															
vel 1 - maximum time at pe	eak temperature du	ring sold	dering is 10-3	0 seconds											
or more information regard	ding material comp	osition p	blease refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	2.73	mg	Supplier	Silicon (Si)	7440-21-3		2.73	mg		
Die Attach	4.85	mg	Supplier	Silver (Ag)	7440-22-4		3.6375	mg		
			Supplier	Epoxy resins	129915-35-1		1.2125	mg		
Lead Frame	75.92	mg	Supplier	Silver (Ag)	7440-22-4		0.7592	mg		
			Supplier	Zinc (Zn)	7440-66-6		0.1518	mg		
			Supplier	Iron (Fe)	7439-89-6		1.9739	mg		
			Supplier	Copper (Cu)	7440-50-8		73.035	mg		
Mold Compound-Black	55.11	mg		Epoxy Phenol Resin	proprietary data		5.7866	mg		
			Supplier	Fused Silica (SiO2)	60676-86-0		49.3234	mg		
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg		
Wire Bond - Au	0.35	mg	Supplier	Gold (Au)	7440-57-5		0.35	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)