


## Specification Sheet

Part Number: 170-03084



Braided Sleeving, Split Wrap, .75" Dia, PET, Orange, 100 ft/ bulk reel

**Article Number**

170-03084

**Type**

BSPSW343B

**Color**

Orange (OG)

**Features & Benefits**

- Split wrap design needs no fasteners and installs quickly, saving assembly time and future accessibility without disassembly.
- Bends to a tight radius without distortion or splitting open.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick access and ability to apply protective sleeving post assembly or post installation situations.

**Quantity Per**

box

**Product Description**

A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

<b>Short Description</b>	Braided Sleeving, Split Wrap, .75" Dia, PET, Orange, 100 ft/ bulk reel
<b>Global Part Name</b>	BSPSW343B-PET-OG
<b>Length L (Imperial)</b>	100.0
<b>Length L (Metric)</b>	30.48
<b>Bundle Diameter Min (Imperial)</b>	0.1
<b>Bundle Diameter Min (Metric)</b>	2.54
<b>Bundle Diameter Max (Imperial)</b>	0.75
<b>Bundle Diameter Max (Metric)</b>	19.1
<b>Diameter D (imperial)</b>	0.75
<b>Diameter D (metric)</b>	19.1
<b>Nominal Diameter (Imperial)</b>	3/4
<b>Nominal Diameter (Metric)</b>	19.1
<b>Wall Thickness WT (Imperial)</b>	0.025
<b>Wall Thickness WT (Metric)</b>	0.64
<b>Material</b>	Polyester (PET)

**Material Shortcut**

PET

**Flammability**

UL 94 V0

**Halogen free**

Yes

**Operating Temperature (Metric)**

-94°F to +257°F (-70°C to +125°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**UL Recognized (US)**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

30.48

**Customs Number**

5808100000

**Weight (Metric)**

0.73

**Weight (Imperial)**

1.6