


PCB LAYOUT
(TopView)

Specification:

1. Electrical Char
 - Insulation Resistance: 500MΩ min. 500V DC for 1 minute
 - Contact Resistance: 30mΩ max.
 - Rating Current: 1.5A max.
 - Rating Voltage: 150V AC
 - Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.
2. Physical Char
 - Housing: PBT Glass filled (UL 94V-0) Color: Black
 - Soldering Temperature: 235°C for 5 sec.
 - Spring Wire: 0.35mm Dia Phosphor Bronze
 - 6u" Gold plating over Nickel
 - Temperature Range: -40°C to +85°C
 - Durability: 750 mating cycles min.
3. Packing: Tray

RoHS compliant
Unit:mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	04.08.2016	Winnie
.XX	±0.20					Approved	17.06.2019	Winnie
.XXX	±0.13							
.XXXX	±0.05							
DIM	TOL	①	Update the dimension	17.06.2019	Segal			
		②	Drawn	04.08.2016	Winnie			
Angle	+0°30'	Id.	Modification	Date	Name			

ASSMANN WSW-No.
A-2004-2-4-N-R

Drawing-No.
ASS 7324 CO rev01

Replace SHEET