



- Material**
- Terminal body (contact pin): Brass(CuZn) Tin plated
 - Insulator (housing): Thermoplastic (UL 94V-0) Green
- Electrical cULus**
- Voltage rating: 300VAC
 - Current rating: 20A
 - Wire range:
 - Solid wire(AWG):
 - Stranded wire(AWG):
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -30°C to +105°C
 - Soldering temperature: 250°C±10°C/5 Sec
 - Safety Approval: (cULus) pending

N=Number of contacts

RoHS compliant

 File No.: E349947

Scale	1:1
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM	TOL
X.°	±1°
Angle	TOL

②	Add the UL File No.	Winnie	19.04.2016
①	Drawn	Dean	10.12.2009
	Modification		
	Date		
	Name		

Drawn	10.12.2009	Dean
Approved	19.04.2016	Winnie

Customer-No.	
ASSMANN WSW-No.	A-TB750-00XXCH
Drawing-No.	ASS 3942 CO
Replace	rev02
Sheet	

1	2	3	4	5	6	7
1	2	3	4	5	6	7
H	G	F	E	D	C	B
H	G	F	E	D	C	B