Data sheet | Item number: 280-434

Operating tool; made of insulating material; 4-way

www.wago.com/280-434





Data Technical data

Main product function	Operating tool
Number of spacings	4 -way

Physical data

Depth	150 mm / 5.91 inches
Pin spacing	5/5.08 mm

Mechanical Data

Suita	le .	for male and female connectors with CAGE CLAMP	connection

Material Data

Fire load	0.717 MJ
Weight	23.7 g

Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 280-434

www.wago.com/280-434



ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	40 (1) pcs
Packaging type	box
Country of origin	DE
GTIN	4017332271912
Customs tariff number	82055980000

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Downloads

Documentation

Bid Text

280-434 X81 - Datei	2019 Feb 19	xml 2.6 kB	Download
280-434 doc - Datei	2017 Sep 11	doc 24.1 kB	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 280-434 URL Download Operating tool; made of insulating material; 4-way

Installation Notes

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 280-434

www.wago.com/280-434





Inserting a male connector via multipole operating tool.

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$