





(1)









Ν	0	ΓЕ	S:	

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC WITHSTANDING VOLTAGE:	1000V AC rms

JUUV AC rms		
	SW REFERENCE NO.: 630 C	OMBO ASSI
	DRAWN: C.B	DATE: JA
	CHECKED:	DATE:



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

EDAC INC TORONTO, ONTARIO YOUR CONNECTION TO QUALITY & SERVICE	THES ARE SHAL OR U MANU WITH

COMBINATION D-SUB

SE DRAWINGS AND SPECIFICATIONS THE PROPERTY OF EDAC INC.,AND ALL NOT BE REPRODUCED,OR COPIED USED AS THE BASIS FOR THE NUFACTURE OR SALE OF APPARATUS HOUT WRITTEN PERMISSION.

DRAWN: C.B DATE: JAN. 01/2019 CHECKED: DATE: DATE: SCALE: (IN C.A.D. 1:1) SHEET 1 OF 2 DRAWING NUMBER: 630-2W2-640-1TA ISSUE 1 1 1 PART NUMBER: 630-2W2-640-1TA ISSUE 1 1 1	SW REFERENCE NO.: 630 COMBO ASSEMBLY		
SCALE: (IN C.A.D. 1:1) SHEET 1 OF 2 DRAWING NUMBER: 630-2W2-640-1TA ISSUE	DRAWN: C.B	DATE: JAN. 01/2019	
DRAWING NUMBER: 630-2W2-640-1TA ISSUE	CHECKED:	DATE:	
	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2	
PART NUMBER: 630-2W2-640-1TA 1	DRAWING NUMBER: 630-2W2	-640-1TA ISSUE	
	PART NUMBER: 630-2W2	-640-1TA 1	

