

DTP4P-L012-GKT ✓ ACTIVE

TE Internal #: DTP4P-L012-GKT

Automotive Seals & Cavity Plugs, Gasket, Closed Cell Sponge,
Black, 4 Position, -70 – 225 °F [-57 – 107 °C]

[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Seals & Cavity Plugs



Connector Seal Type: **Gasket**

Seal Material: **Closed Cell Sponge**

Operating Temperature (Max): **107 °C [225 °F]**

Contains Lubricant: **No**

Primary Product Color: **Black**

Features

Product Type Features

Connector Seal Type	Gasket
---------------------	--------

Configuration Features

Number of Positions	4
---------------------	---

Body Features

Seal Material	Closed Cell Sponge
---------------	--------------------

Primary Product Color	Black
-----------------------	-------

Usage Conditions

Operating Temperature (Max)	107 °C[225 °F]
-----------------------------	----------------

Operating Temperature Range	-57 – 107 °C[-70 – 225 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94HBF
------------------------	----------

Packaging Features

Packaging Method	Box
------------------	-----

Other

Contains Lubricant	No
--------------------	----

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought



TE Part #DT06-12SA-E003
PLG, 12P, GRY, N, CAP, A



TE Part #WP-4P
WEDGE LOCK, 4P, REC, ORG, DTP



TE Part #2-1564514-1
Heavy Duty Sealed Connector Series
Housings



TE Part #HDP24-24-35SN-L017
REC, 35P, BLK, N, RNG, 16/20, S



TE Part #DTP04-4P-L012
REC, 4P, GRY, N, FLANGE



TE Part #DT4P-L012-GKT
GASKET, 4P, BLK, DT/DTM



TE Part #DT8P-L012-GKT
GASKET, 8P, BLK, DT/DTM



TE Part #967011-1
EINZELADERDICHTUNG



TE Part #DT12-L012-GKT
GASKET DT 12 WY FLD RC

Documents

Product Drawings

GASKET, 4P, BLK, DTP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DTP4P-L012-GKT_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DTP4P-L012-GKT_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DTP4P-L012-GKT_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

DTP4P-L012-GKT

Automotive Seals & Cavity Plugs, Gasket, Closed Cell Sponge, Black, 4 Position, -70 – 225 °F [-57 – 107 °C]



CONNECTOR SELECTOR

English