


GR900 SMD Space, Ceramic, 0.01 uF, 10%, 50 VDC, BX, N/A, 0805



Click here for the 3D model.

0805
2.03mm +/-0.38mm (0.08 in +/-0.015 in)
1.27mm +/-0.38mm (0.05 in +/-0.015 in)
1.4mm MAX (0.055 in MAX)
0.51mm +/-0.25mm (0.02 in +/-0.01 in)

General Information Series GR900 SMD Space Style SMD Chip RoHS Yes Gold Termination Failure Rate N/A **Testing and Reliability** GR900 CSAM A AEC-Q200 No 78 Weeks Shelf Life MSL 1

Specifications	/
Capacitance	0.01 uF
Capacitance Tolerance	10%
Voltage DC	50 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BX

Packaging Specifications

Packaging

Bulk, Bag

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.