

Desktop Computer Power Cord, NEMA 5-15P to C13, 5-Pack - 10A, 125V, 18 AWG, 2 ft. (0.61 m), Black

MODEL NUMBER: P030-002-5



Computer power cables connect your server, switch, router and other devices to a surge protector, PDU or UPS system with 5-15R outlets.

Features

Desktop Computer Power Cords Connect Essential Network Equipment This computer power supply cable is designed for keeping mission-critical network equipment operating at all times. You can use it to connect a computer, monitor, printer, server, switch, router or other device with a C14 power inlet to an AC wall outlet, surge protector, UPS system or PDU. The 2-ft. (0.61 m) length helps reduce cable clutter and minimize the risk of tripping. Five power supply cables are included.

Specifications

| OVERVIEW | |
|-----------------------------|---|
| UPC Code | 037332143280 |
| Device Compatibility | Computer; Monitor/HDTV; Printer; Server; Network Switch; Router; UPS; PDU |
| Country/Region | North America |
| INPUT | |
| Maximum Input Amps | 10 |
| Voltage Compatibility (VAC) | 125 |
| PHYSICAL | |
| Plug Color | Black |
| Cable Jacket Color | Black |

Highlights

- Recommended for powering servers, switches, routers and other network devices
- 2-ft. (0.61 m) length allows flexibility in placing devices, while avoiding cable clutter
- Ideal replacements for worn-out or missing NEMA 5-15P to C13 power cables

Applications

- Connect devices like servers, switches and routers to a PDU in your data center
- Extend existing power connections up to 2-ft. (0.61 m) to more easily place devices or reach a power source
- Provide high-quality replacements for worn-out or missing power cords

Package Includes

- P030-002-5 Desktop Computer Power Cord, NEMA 5-15P to C13, 5-Pack, 2-ft. (0.61 m), Black

| | |
|--------------------------------------|-----------------------------|
| Cable Jacket Material | PVC |
| Cable Jacket Rating | FT2 |
| Power Cord Jacket Type | SJT |
| Cable Outer Diameter (OD) | 7.7mm |
| Number of Conductors | 3 |
| Wire Gauge (AWG) | 18 |
| Wire Gauge (OD - mm ²) | 0.82 |
| Cable Length (ft.) | 2 |
| Cable Length (m) | 0.61 |
| Shipping Dimensions (hwd / in.) | 9.98 x 7.09 x 0.50 |
| Shipping Dimensions (hwd / cm) | 25.35 x 18.01 x 1.27 |
| Shipping Weight (lbs.) | 1.10 |
| Shipping Weight (kg) | 0.50 |
| Unit Dimensions (hwd / in.) | 0.000 x 0.000 x 0.000 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range | 20% to 80% RH |
| Storage Humidity Range | 20% to 80% RH |
| CONNECTIONS | |
| Side A - Connector 1 | NEMA 5-15P |
| Side B - Connector 1 | IEC-320-C13 |
| FEATURES & SPECIFICATIONS | |
| Antibacterial | No |
| Angled Plug | No |
| High Voltage | No |
| Locking Plug | No |
| Coiled Power Cord | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | cUL Listed; UL Listed |
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |



1000 Eaton Boulevard
Cleveland, OH 44122
United States

| | |
|--|---------------------------|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
|--|---------------------------|



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.