



Data

Technical data

Main product function	Operating tool
Number of spacings	1 -way

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Physical data

Depth	50 mm / 1.97 inches
Pin spacing	5/7.62 mm

Mechanical Data

Suitable	for male and female connectors with CAGE CLAMP® connection
----------	--

Material Data

Color	natural
Material group	I
Insulation material	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	HB
Fire load	0.038 MJ
Weight	1.4 g

Commercial data

Product Group	3 (Multi Conn. System)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4017332117661
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates


General approvals

Logo	Approval	Additional Approval Text	Certificate name
	CSA DEKRA Certification B.V.	C22.2	1466354

Subject to changes. Please also observe the further product documentation!



Approvals for marine applications

Logo	Approval	Additional Approval Text	Certificate name
	LR Lloyds Register	IEC 61984	96/20035 (E5)

Downloads

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 231-159	URL	Download
Operating tool; natural		

Installation Notes



Conductor termination parallel to CAGE
CLAMP® actuation

Subject to changes. Please also observe the further product documentation!



Conductor termination perpendicular to CAGE
CLAMP® actuation

Subject to changes. Please also observe the further product documentation!