	T G	п	m		0	D	A		
4 ω	R 22.6 Max () () () () () () () () () () () () ()	S	ØA			AYOUT SHOWN AS EXAMPLE			4
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown as e	xample Connector dimension Dim Nominal						
N	-Shell Material: Aluminium-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories		A       34.9±0.3         B       19.07+0.1/-0.15         R       32.5Max         S       31.8±0.4         W       2.2+0.9/-0.1         /V THREAD       M15x1-6g		due to a us the Specification (profes	Il not be liable for any non-conform se of the Products which does not consisted by either of the Parties or resional recommendation, technical recommendation <u>Country</u> Juris FR PN: 8D711Z04BD	omply with by a third party		2
_	-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours-Mass: 21.05 g ± 10%			ISS D Designed By:	0-2016 First Release ATE Latest modificat Date	2:	CUSTOMER DRAWING	MOD N°	
	BASIC SERIES:       8D       7       -       11       Z       0         SHELL TYPE : Jam nut Receptacle	4 B D	ORIENTATION CONTACT TYPE : SOCKET(500 Matin CONTACT LAYOUT : 11	ngs)		Aluminium Receptad	NPRDS / PROJECT 859 This document is the pro SOURIAU it must not be reproduc communicated without pe	ced or	1
	H G	F	E	D A3	C	8D711Z04BD-C	A	1/2	

Г	٦ D	т (П		A					
4	Contact Layout $ \begin{array}{c}                                     $		Panel cutout JAM NUT RECEPTACLE (TYPE 7)	4					
	(Insert arrangement 11-4)           Contact position ID         Contact location           A         +.065 (1.65)         +.065 (1.65)           B         +.065 (1.65)        065 (1.65)           C        065 (1.65)        065 (1.65)           D        065 (1.65)         +.065 (1.65)           Shell         Arrangement no.         Number of contacts         Size contacts         Service rating         Contact         Supersedes           11         -4         4         20         I         All         MS20050-4								
ى			DimNominalB19.59+0/-0.25ØC20.96+0.25/-0	3					
	_		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with						
			the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
D			FR Not Listed PN: 8D711Z04BD	2					
			A     01-10-2016     First Release       ISS     DATE     Latest modification - by	MOD N°					
		Designed By:     Date:     CUSTOMER DRAWING       TITLE     Aluminium Receptacle 8D series							
<b>→</b>			SCALE     General linear     NPRDS / PROJECT       NA     Image: scale s	1					
			SOURIAU WWW.SOURIAU.COM	communicated without permission					
		1	FORMATSOURIAU DRG N°A38D711Z04BD-C	SHEET 2/2					
L	H G	F E	D C B	Α					