



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 59.6              |
| B   | 22.2              |
| C   | 4                 |
| D   | 33.8              |
| E   | 52.6              |
| F   | 49.2              |
| G   | 63.5              |
| H   | 4.3               |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 8   | DOSENGEHÄUSE / SHELL                    |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

| Material Specification:                        |
|--|
| Shell Material: Aluminium alloy                |
| Shell Plating: Zinc cobalt, green (conductive) |
| Insulator Material: CR-Elastomere              |
| Contact Material: Copper alloy                 |
| Contact Plating: Hard silver                   |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
**CUSTOMER**

description **CA3102E36-3SWB-01-A233**  
 Box mounting receptacle

**ITT**  
 Engineered for life  
 ITT CANNON GmbH  
 D - 71384 Weinstadt/Germany

Metric Crimp / Socket / Layout: 36-3

© All rights reserved. Reproduction or issue to third in any form  
 whoever is only permitted with written authorization of ITT Cannon

page 1/1  
 revision 1730 14. May 19