

## STRADELLA-IP-28-HB-M

~65° medium beam. Variant made from PMMA.

### TECHNICAL SPECIFICATIONS:

Dimensions	100.0 x 100.0 mm
Height	9.5 mm
Fastening	pin, screw
Ingress protection classes	IP67
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
STRADELLA-IP-28-HB-M	Multi-lens	PMMA	clear	
STRADELLA-28-SEAL	Seal	Silicone	white	

### ORDERING INFORMATION:













Component		Qty in box	MOQ	MPQ	Box weight (kg)
CS16323_STRADELLA-IP-28-HB-M	Multi-lens	156	78	78	5.8
» Box size: 476 x 273 x 247 mm					





See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)



#### PHOTOMETRIC DATA (MEASURED):

<p></p> <p>LED                    HiQLED STR28 CR JE2835 4x7 xxx</p> <p>FWHM / FWTM        56.0° / 113.0°</p> <p>Efficiency             92 %</p> <p>Peak intensity        0.7 cd/m</p> <p>LEDs/each optic     1</p> <p>Light colour         White</p> <p>Required components:</p>		
<p></p> <p>LED                    HiQLED STR28 CR JĐš3030 4x7 xxx</p> <p>FWHM / FWTM        55.0° / 112.0°</p> <p>Efficiency             92 %</p> <p>Peak intensity        0.7 cd/m</p> <p>LEDs/each optic     1</p> <p>Light colour         White</p> <p>Required components:</p>		
<p></p> <p>LED                    QUICK FLUX STR28 XD2x14 xxx G8</p> <p>FWHM / FWTM        71.0° / 126.0°</p> <p>Efficiency             92 %</p> <p>Peak intensity        0.5 cd/m</p> <p>LEDs/each optic     1</p> <p>Light colour         White</p> <p>Required components:</p>		
<p></p> <p>LED                    QUICK FLUX STR28 XP2x14 xxx G7</p> <p>FWHM / FWTM        71.0° / 127.0°</p> <p>Efficiency             94 %</p> <p>Peak intensity        0.6 cd/m</p> <p>LEDs/each optic     1</p> <p>Light colour         White</p> <p>Required components:</p>		



#### PHOTOMETRIC DATA (MEASURED):




LED QUICK FLUX STR28 XT2x14 xxx G5  
 FWHM / FWTM 70.0° / 126.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED J Series 2835  
 FWHM / FWTM 56.0° / 113.0°  
 Efficiency 92 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED J Series 3030  
 FWHM / FWTM 55.0° / 112.0°  
 Efficiency 92 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED J Series 3030  
 FWHM / FWTM 61.0° / 119.0°  
 Efficiency 95 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):



#### CREE

LED XD16  
 FWHM / FWTM 71.0° / 126.0°  
 Efficiency 92 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### CREE

LED XP-G3  
 FWHM / FWTM 71.0° / 127.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### CREE

LED XT-E  
 FWHM / FWTM 70.0° / 126.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### NICHIA



LED NF2W585AR  
 FWHM / FWTM 67.0° / 125.0°  
 Efficiency 93 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### PHOTOMETRIC DATA (MEASURED):





LED NF2W585AR  
 FWHM / FWTM 68.0° / 126.0°  
 Efficiency 93 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED NVSW219F  
 FWHM / FWTM 69.0° / 125.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED NVSW319B  
 FWHM / FWTM 74.0° / 126.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED OSCONIQ S 3030  
 FWHM / FWTM 57.0° / 118.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### PHOTOMETRIC DATA (MEASURED):

#### OSRAM



Opto Semiconductors

LED OSLON Square CSSRM2/CSSRM3  
 FWHM / FWTM 62.0° / 122.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### SAMSUNG

LED HiLOM SC28 (LH181B)  
 FWHM / FWTM 57.0° / 111.0°  
 Efficiency 91 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### SAMSUNG

LED HiLOM SM28 (LM301B)  
 FWHM / FWTM 58.0° / 115.0°  
 Efficiency 93 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



SEOUL SEMICONDUCTOR


LED Z5M3  
 FWHM / FWTM 67.0° / 125.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### PHOTOMETRIC DATA (SIMULATED):




LED J Series 5050 Round LES  
 FWHM / FWTM 70.0° / 120.0°  
 Efficiency 95 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




LED XP-G2 HE  
 FWHM / FWTM 74.0° / 126.0°  
 Efficiency 95 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED LUXEON 3030 2D (Round LES)  
 FWHM / FWTM 58.0° / 118.0°  
 Efficiency 92 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED LUXEON 5050 Round LES  
 FWHM / FWTM 69.0° / 120.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:






#### PHOTOMETRIC DATA (SIMULATED):


##### LUMILEDS

LED LUXEON 5050 Square LES  
 FWHM / FWTM 70.0° / 120.0°  
 Efficiency 95 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




##### NICHIA

LED NF2x757G  
 FWHM / FWTM 63.0° / 119.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




##### NICHIA

LED NF2x757G  
 FWHM / FWTM 63.0° / 119.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:







##### NICHIA

LED NVSxE21A  
 FWHM / FWTM 65.0° / 118.0°  
 Efficiency 93 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (SIMULATED):


<p><b>NICHIA</b></p> <p>LED NVSxx19B/NVSxx19C            FWHM / FWTM 73.0° / 122.0°            Efficiency 95 %            Peak intensity 0.6 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED Duris S5 (2 chip)            FWHM / FWTM 64.0° / 119.0°            Efficiency 94 %            Peak intensity 1 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED Duris S8            FWHM / FWTM 67.0° / 118.0°            Efficiency 94 %            Peak intensity 0.7 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSCONIQ C 2424            FWHM / FWTM 68.0° / 118.0°            Efficiency 95 %            Peak intensity 0.7 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	

#### PHOTOMETRIC DATA (SIMULATED):

#### OSRAM

Opto Semiconductors


LED OSCONIQ P 3030  
 FWHM / FWTM 56.0° / 119.0°  
 Efficiency 96 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OSRAM


Opto Semiconductors

LED OSCONIQ P 3737 (2W version)  
 FWHM / FWTM 68.0° / 121.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### SAMSUNG

LED LH181B  
 FWHM / FWTM 65.0° / 117.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### SAMSUNG


LED LH351B  
 FWHM / FWTM 71.0° / 119.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (SIMULATED):


#### SAMSUNG

LED LH351C  
 FWHM / FWTM 75.0° / 119.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### SAMSUNG

LED LM28xB Series  
 FWHM / FWTM 66.0° / 119.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### SAMSUNG

LED LM301B  
 FWHM / FWTM 63.0° / 118.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



SEOUL SEMICONDUCTOR





LED SEOUL 3030  
 FWHM / FWTM 69.0° / 120.0°  
 Efficiency 95 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (SIMULATED):

<p><b>SEOU</b> SEOU SEMICONDUCTOR</p> <p>LED: SEOUL DC 3030</p> <p>FWHM / FWTM: 68.0° / 120.0°</p> <p>Efficiency: 96 %</p> <p>Peak intensity: 0.6 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p><b>SEOU</b> SEOU SEMICONDUCTOR</p> <p>LED: SEOUL DC 5050 6V</p> <p>FWHM / FWTM: 69.0° / 120.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 0.7 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p><b>SEOU</b> SEOU SEMICONDUCTOR</p> <p>LED: Z5M1/Z5M2</p> <p>FWHM / FWTM: 70.0° / 122.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 0.6 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p><b>SEOU</b> SEOU SEMICONDUCTOR</p> <p>LED: Z8Y19</p> <p>FWHM / FWTM: 65.0° / 117.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 0.7 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	

#### PHOTOMETRIC DATA (SIMULATED):

<p> SEOU SEMICONDUCTOR</p> <p>LED: Z8Y22</p> <p>FWHM / FWMT: 76.0° / 130.0°</p> <p>Efficiency: 92 %</p> <p>Peak intensity: 0.6 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p> SEOU SEMICONDUCTOR</p> <p>LED: Z8Y22T</p> <p>FWHM / FWMT: 69.0° / 118.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 0.6 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	

#### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)