

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GQM22M5C2H150GB01# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

41.0mg

http://www.murata.com/en-us/products/productdetail?partno=GQM22M5C2H150GB01%23

References

Specifications

180Embossed Tape

330Embossed Tape

Packaging

Mass (typ.)

1 piece

L

Κ

GQM22M5C2H150GB01K




< List of part numbers with package codes > GQM22M5C2H150GB01L GQM22M5C2H150GB01K

Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment,Industrial Equipment,Mobile Electronics,Medical equipment [GHTF A/B/C] except for implant equipment,Automotive infotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.	

Appearance & Shape





1 of 2

Standard

Packing Quantity

1000

4000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GQM22M5C2H150GB01K

Note: This datasheet may be out of date. Please download the latest datasheet of GQM22M5C2H150GB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GQM22M5C2H150GB01%23

"#" indicates a package specification code.



Specifications

Length	2.8±0.5mm
Width	2.8±0.4mm
Thickness	1.15±0.2mm
Capacitance	15pF ±2%
Distance between external terminals g	1.0mm min.
External terminal size e	0.3mm min.
Operating Temperature Range	-55℃ to 125℃
Rated Voltage	500Vdc
Size code in inch(mm)	1111 (2828M)
TC	0±30ppm/°C
Temperature characteristics (complied standard)	C0G(EIA)
Temperature range of temperature characteristics	25℃ to 125℃

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

