

## R75MF2330JH30K

Aliases (75MF2330JH30K)

R75, Film, Metallized Polypropylene, Automotive Grade, 0.033 uF, 10%, 400 VDC, 85°C, Lead Spacing = 10mm



Click [here](#) for the 3D model.

### Dimensions

|    |                   |
|----|-------------------|
| L  | 13mm +0.2/-0.5mm  |
| H  | 11mm +0.1/-0.5mm  |
| T  | 5mm +0.2/-0.5mm   |
| S  | 10mm +/-0.4mm     |
| LL | 3.2mm +0.3/-0.2mm |
| F  | 0.6mm +/-0.05mm   |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 1300      |

### General Information

|                |  |
|----------------|--|
| Series         | R75  |
| Dielectric     | Metallized Polypropylene                         |
| Style          | Radial   |
| Features       | Automotive Grade, Pulse                          |
| RoHS           | Yes  |
| Lead           | Cut  |
| Qualifications | AEC-Q200   |
| AEC-Q200       | Yes  |
| Miscellaneous  | Above 85C DC And AC Voltage Derating Is 1.25%/C. |

### Specifications

|                       |  |
|-----------------------|--|
| Capacitance           | 0.033 uF                               |
| Capacitance Tolerance | 10%                                    |
| Voltage AC            | 220 VAC                                |
| Voltage DC            | 400 VDC                                |
| Temperature Range     | -55/+105°C                             |
| Rated Temperature     | 85°C                                   |
| Dissipation Factor    | 0.04% 1kHz, 0.06% 10kHz, 0.25% 100kHz  |
| Insulation Resistance | 100 GOhms                              |
| Max dV/dt             | 1300 V/us                              |
| Resistance            | 10.6 mOhms (100kHz)                    |
| Ripple Current        | 2.93 Amps (100kHz 85C), 43 Amps (Peak) |
| Inductance            | 9 nH                                   |