


TOLERANCE<br/>UNLESS OTHERWISE<br/>SPECIFIED.X±0.25.XX±0.13.XXX±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER


ORIGINAL



## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED



## OPERATING TEMPERATURE:


POWER/CO-AX CONTACT RATING: 10A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE: 10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

-55°C ~ 125°C

1000V AC rms



|  | COMBINATION D-SUB  |                          | SW REFERENCE NO.: 630 COMBO ASSEMBLY |       |  |  |
|--|--|--------------------------|--------------------------------------|-------|--|--|
| COMBINATION  |  |                          | DATE: JAN. 01/20                     | 19    |  |  |
|  |  |                          | DATE:                                |       |  |  |
| EDAG INC<br>TORONTO, ONTARIO<br>CANADA<br>YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)   | SHEET 1 OF                           | 2     |  |  |
|  |  | DRAWING NUMBER: 630-8W8- | -240-1N3                             | ISSUE |  |  |
|  |  | PART NUMBER: 630-8W8     | -240-1N3                             | 1     |  |  |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

