

т	۵	н т	m	0







LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

ယ

-Standard : Based on MIL-DTL-38999 Series III

SHELL TYPE : Square Flange Receptacle

SHELL SIZE : 11

PLATING : F = Nickel

Н

CONTACT TYPE : Standard Crimp Contact

		: Aluminium	Р				
ľ			PP				
	-Shell Plating	: Nickel	R1				
	-Insulator	: Thermoplastic	R2				
	-Contacts	: Copper Alloy	S V				
	-Seals & Grommet	: Silicon Elastomer	W				
\sim	-Contact Plating	: Gold over copper Alloy 0.8µm minimum	Z				
	-Durability	: 500 Mating cycles	VV THREAD				
	-Delivered without Sou						
	-Temperature Range	-65°C to +200°C					
	-Salt Spray	: 48 hours					
	-Mass	: 11.16 g ± 10%					
	BASIC SERIES:	8D 0 - 11 F 05 P D	L				
			-				

G

F

Connector dimension			
Dim	Nominal		
Р	3.25±0.2		
PP	4.93±0.2		
R1	20.62		
R2	18.26		
S	26.2±0.3		
V	20.83+0/-1.25		
W	2.1/2.5		
Z	31.5 Max		
VV THREAD	M15x1-6g		

Delivered W/O Contacts

CONTACT LAYOUT : 11-05

CONTACT TYPE : PIN(500 Matings)

Е

ORIENTATION : D

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recommend



	σ		А		_	
					4	
AS EXA	MPLE				3	
s whic er of tl	non-conformit h does not co he Parties or t n, technical no	mply with by a third par	ty			
untry		liction & Cont	trol List]		
FR 1F0	Not Listed					
				MOD N°		
		CUSTOME	R DRAWING			
um	um Receptacle 8D series					
ar :	NPRDS / PROJECT 859					
J.CC	COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
AU DRG N° F05PDL-C				SHEET		
103	B		A	, -	J	

	т	۵	п	m	D	0
		Contact Layout				Panel Cutou
4	×	$ \begin{array}{c} & & & \\ & $			Τ	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
	Conta positio ID A B C C D E Shell Arrangement Numb	X-axis Y-axis (mm) +065 (1.65) +056 (1.42) +.113 (2.87) 065 (1.65) +.000 (0.00) 130 (3.30) 113 (2.87) 065 (1.65) 065 (1.65) +.056 (1.42)	1		₹ ₩	
ى ى	size no. conta 11 -5 5					Dim ØA ØAA R1 ØT
	_					
	a					SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either or (professional recommendat
N						PN: 8D011F
					A 14-10-	2016 First Release
					ISS DA Designed By:	TE Latest modification - by Date:
					SCALE	
_					NA	General linear Tolerances:
					SOURI	WWW.SOURIAU.C
				_	FORMAT A3	SOURIAU 8D011F0
	Н	G	F	E	D	С

