ב בר			0	œ			
A Z ØS						4	
	Keying Shown as example		LAYOUT SHOWN AS EX	CAMPLE		3	
CHARACTERISTICS	Connector dimension						
-Standard : Based on MIL-DTL-38999 Series III	DimNominalØS29.4 Max						
<ul> <li>Shell Material : Aluminium</li> <li>Shell Plating : Black Zinc Nickel</li> <li>Insulator : Thermoplastic</li> <li>Contacts : Copper Alloy</li> <li>Seals &amp; Grommet : Silicon Elastomer</li> <li>Contact Plating : Gold over copper Alloy 0.8µm minimum</li> </ul>	-Shell Material       : Aluminium         -Shell Plating       : Black Zinc Nickel         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy         -Seals & Grommet       : Silicon Elastomer						
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	FR         Not Listed         2           PN: 8D513Z03SD         2						
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 19-10-2016	First Release				
		ISS DATE Designed By:	Latest modification - by Date:	CLICT		<u>N°</u>	
		TITLE	Date: CUSTOMER DRAWING Aluminium Plug 8D series				
ASIC SERIES: 8D 5 - 13 Z 03 SHELL TYPE : Plug with RFI Shielding	S D	SCALE -{	General linear Tolerances:	NP	PRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIENTATION : D CONTACT TYPE : SOCKET(500 Matings)	: D SOURIAU WWW.SOURIAU.COM This document is the prop SOURIAU it must not be reproduce					
PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 13-03		SOURIAU		SHEE	T	
		A3	8D513Z0		1/2		
H G	F I E	D	C	В	A		

A 19-10-2016 First Release ISS DATE Latest modification - by Designed By: Date:									-
03 316 The transformation of the folder o		T	Q	г	m	D		0	
Source and the product of the second control			Contact Layout						
13-03         Tree         A         23         147             SUBRAU shall not be fished for dide to a use of the Products the Specification study within (professional recomment (professional recomme	4								
To SOURIAU shall not be liable for the specifications issued by ether (professional recommend (professional recommend PN: 8D513 A 19-10-2016 first Release Totes Na SOURIAU SOURIAU TITLE Alum SOURIAU Commend SOURIAU TOTES Commend SOURIAU Commend SOURIAU Commend SOURIAU Commend SOURIAU		A B	13-03           X         Y           2.39         1.47           0         -2.79						
Lo Court Lo Court Lo Court Lo Court Lo Court Lo Court PN: 8D51: A 19-10-2015 First Release ISS DATE Latest modification - by Designed By: Date: TITLE Alum SCALE Out NA General Inear Tolerances: 2 SOURIAU WWW.SOURIAU.	ယ		2.03						
Lo Court Lo Court Lo Court Lo Court Lo Court Lo Court PN: 8D51: A 19-10-2015 First Release ISS DATE Latest modification - by Designed By: Date: TITLE Alum SCALE Out NA General Inear Tolerances: 2 SOURIAU WWW.SOURIAU.									
A       19-10-2016       First Release         ISS       DATE       Latest modification - by         Designed By:       Date:         TITLE       Alum         SCALE       Image: Comparison of the second							d	ue to a use of the ecifications issued	Products v d by either
A 19-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: TITLE Alum SCALE NA General linear Tolerances: ± SOURIAU FORMAT SOURIAU	N								Coun
ISS DATE Latest modification - by Designed By: Date: TITLE Alum SCALE NA CALE NA CONTAU FORMAT SOURIAU.								PN: 8	8D513
Designed By:     Date:       TITLE     Alum       SCALE     General linear       NA     Image: Designed By:       SOURIAU     Tolerances:       ±     SOURIAU       FORMAT     SOURIAU									
SCALE NA SOURIAU FORMAT SOURIAU SOURIAU SOURIAU									
NA TOIErances: ± SOURIAU WWW.SOURIAU. FORMAT SOURIAI						ТІТ	LE		Alumi
FORMAT SOURIA	<b>_</b>								olerances:
FORMAT SOURIA A3 8D5132						SOUF	RIAU	WWW.SOL	JRIAU.
					_			SO 8	URIAU D5132

G

Н

F

Е

D

С

