



## TS-230 (Legacy)

**CPU** Realtek RTD1296 4-core 1.4GHz processor

**CPU Architecture** 64-bit ARM

**Floating Point Unit** Yes

**Encryption Engine** Yes

**Hardware-accelerated Transcoding** Yes

**System Memory** 2 GB DDR4, not expandable

**Maximum Memory** 2 GB DDR4, not expandable

**Flash Memory** 4 GB (Dual boot OS protection)

**Drive Bay** 2 x 3.5-inch SATA 6Gb/s, 3Gb/s

**Drive Compatibility** 3.5-inch SATA hard disk drives  
2.5-inch SATA hard disk drives  
2.5-inch SATA solid state drives

**Hot-swappable** Yes

**Gigabit Ethernet Port (RJ45)** 1

**Wake on LAN (WOL)** Yes

**Jumbo Frame** Yes

**USB 2.0 port** 1

**USB 3.2 Gen 1 port** 2

**Form Factor** Tower

**LED Indicators** System Status, LAN, USB, HDD1~2

**Buttons** Power, Reset, USB Copy

**Dimensions (HxWxD)** 7.43 × 3.55 × 6.15 inch

Weight (Net)	4.37 lbs
Weight (Gross)	4.43 lbs
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	65W Adapter, AC 100-240V
Power Consumption: HDD Sleep Mode	4.48 W
Power Consumption: Operating Mode, Typical	12.277 W
Fan	1 x 80mm, 12VDC
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	200

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.