



# Raychem INSTALITE ZH-150 Sleeving

High-Temperature 150°C Zerohal Heat-Shrinkable Lightweight Tubing

## LIGHTWEIGHT

- Lightweight crosslinked material
- Halogen free, flame retardant, fluid resistant
- Ruggedized, abrasion resistant
- Operating temperature range: -75°C to 150°C

## VERSATILE

- 2 to 1 shrink ratio, in eight sizes
- Limited fire hazard
- Metric sizing

## EASE OF USE

- Highly flexible for easy handling
- Single system for multiple application environments

## APPLICATIONS

- Military
- Marine
- Rail and Mass Transit

TE's INSTALITE ZH-150 heat-shrinkable tubing combines high-temperature and zero halogen properties in a lightweight material and helps you meet all requirements for zero halogen, limited fire hazard tubing with high-temperature properties.

The tubing helps provide excellent mechanical and electrical protection for wire and cable harnesses across multiple environments.

This advancement in material science provides a heat-shrink product that can deliver protection for people and equipment in a high-temperature, lightweight product.

## TE Components . . . TE Technology . . . TE Know-how . . .

AMP | AGASTAT | CII | HARTMAN | KILOVAC | MICRODOT | NANONICS | POLAMCO | Raychem  
SEACON | | Rochester | DEUTSCH

Empower Engineers to Solve Problems, Moving the World Forward.

# INSTALITE ZH-150 Sleeving

Lightweight High-Temperature, Zerohal Heat-Shrinkable Tubing



## Performance Characteristics

### MATERIALS

- **Lightweight, crosslinked material:** Zerohal material, flame retarded

### ENVIRONMENTAL/MECHANICAL

- **Operating Temperature Range:** -75°C to 150°C
- **Flammability:** Limited fire hazard
- **Fluid Resistance:** Resists common aerospace and military fluids
- **Flexibility:** Very flexible tubing
- **Mechanical:** Ruggedized, abrasion resistant
- **Shrink Ratio:** 2 to 1
- **Minimum Shrink Temperature:** 150°C
- **Minimum Full Recovery Temperature:** 175°C

### STANDARDS/SPECIFICATIONS

- **Application Specification:** ELE-3COP-551
- **Product Specification:** RW-3044

## ORDERING INFORMATION

Description	Part No.	Size	Inside Diameter		Wall Thickness After Recovery (nom.)	Mass Grams/m (±10%)
			As Supplied (min.)	After Recovery (max.)		
ZH150-3/1.5-0-SP	EH3261-000	3.0/1.5	3.0 (0.118)	1.5 (0.059)	0.70 (0.028)	4.2
ZH150-5/2.5-0-SP	EH3263-000	5.0/2.5	5.0 (0.197)	2.5 (0.098)	0.75 (0.030)	8.92
ZH150-8/4-0-SP	EH3264-000	8.0/4.0	8.0 (0.315)	4.0 (0.157)	0.80 (0.031)	13.00
ZH150-12/6-0-SP	EH3265-000	12.0/6.0	12.0 (0.472)	6.0 (0.236)	0.90 (0.035)	20.94
ZH150-18/9-0-SP	EH3267-000	18.0/9.0	18.0 (0.709)	9.0 (0.354)	1.00 (0.039)	31.96
ZH150-24/12-0-SP	EH3268-000	24.0/12.0	24.0 (0.945)	12.0 (0.472)	1.10 (0.043)	50.69
ZH150-40/20-0-SP	EH3269-000	40.0/20.0	40.0 (1.575)	20.0 (0.789)	1.30 (0.051)	94.1
ZH150-50/30-0-SP	EH3270-000	50.0/30.0	50.0 (1.969)	30.0 (1.181)	1.50 (0.059)	160

Dimensions: mm (inch)

## INSTALITE ZH-150 COMPARISON

	Temperature Range	Low Smoke	Flexibility	Low Toxicity	Light Weight	Fluid Resistance
<b>ZH-150</b>	Excellent	Very Good	Excellent	Very Good	Excellent	Excellent
<b>ZHTM</b>	Good	Excellent	Good	Excellent	Good	Good
<b>DR25</b>	Excellent	—	Excellent	—	Very Good	Excellent

[te.com/zh150](http://te.com/zh150)

© 2018 TE Connectivity Ltd. family of companies. All Rights Reserved.

1-1773896-9 03/18

AMP, AGASTAT, CII, DEUTSCH, HARTMAN, INSTALITE, KILOVAC, LL Rowe, MICRODOT, NANONICS, POLAMCO, Raychem, SEACON, Zerohal, TE, TE Connectivity and the TE connectivity (logo) are trademarks.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.

North America +1 800 522 6752 • Asia Pacific +86 0 400 820 6015 • France +33 1 34 20 86 86 • Germany +49 6251 133 1999 • United Kingdom +44 800 267 666  
Visit [te.com](http://te.com) for additional country contacts.