


NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


WITHSTANDING VOLTAGE:

THERMOPLASTIC POLYESTER, UL94V-0 COPPER ALLOY, 30µ" GOLD PLATED



OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	50Ω (IMPEDANCE)
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE: DIELECTRIC	$5000M\Omega$ min.

.XX ±0.13 .XXX ±0.05



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY		
COMBINATION			DATE: JAN. 01/201	19	
			DATE:		
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
CUFUS TORONTO, ONTARIO CANADA	MANUFACTURE OR SALE OF APPARATUS	DRAWING NUMBER: 629-36W4640-5NB		ISSUE	
		PART NUMBER: 629-36W4	4640-5NB	1	

1000V AC rms



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

EDAC INC TORONTO, ONTARIO CANADA) QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICAT ARE THE PROPERTY OF EDAC INC.,/ SHALL NOT BE REPRODUCED,OR CC OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPAR. WITHOUT WRITTEN PERMISSION.

STEEL, TIN PLATED

