BGA Heat Sink - High Performance Straight Fin w/Thermal Tape





ATS Part#: **ATS-54250D-C1-R0**

Description: 25.00 x 25.00 x 9.50 mm BGA Heat Sink - High Performance Straight Fin w/Thermal

Tape

Heat Sink Type: Straight Fin
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-54250D-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Designed specifically for BGAs and other surface mount packages
- · Comes preassembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	15.3 °C/W	11.6 °C/W	9.8 °C/W	8.7 °C/W	8 °C/W	7.4 °C/W	6.9 °C/W
	Ducted Flow	7.3	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
	25.00 mm	25.00 mm	9.50 mm	N/A mm	T412	BLACK-ANODIZED
*Image above is for illustration purpose only.	 Dimension ATS-5428 (Saint-Go Thermal papplicatio ATS reserver ATS certification 	50D-C2-R0 is the exbain C675). Derformance data aren. The right to updance.	height from the botto eact heat sink assem e provided for reference ate or change its pro-	om of the base to the base to the bly with an equivale ence only. Actual perioducts without notices and REACH contable.	ent therma	al interface material e may vary by



