ASSOCIATION CONNECTING LECTRONICS INDUSTRIES	ockburn, Illinois, A	ll rights reserved untions.	ander both	This docume evel parts, t	ent is a declaration en declaration en	on of the su	bstances all lower	within the manufactur r level materials for w	er listed i hich the n	tem. Note: nanufacture	if the item is an as r has engineering	sembly with lower responsibility.	
52-21.1 IPC Web Site for Information on IPC-1752 Standard Form Type Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials					als and M	ls and Mfg Information			
Supplier Information													
Company name* Company unique ID				Unique ID Authority				Response Date*					
nsemi										2023-06-08			
Contact Name	Title - Contact]	Phone - Contact*				Email - Contact*				
Product-Env-Stewards	duct-Env-Stewards Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representative]	Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product Enviro Complia			Compliance			NA				Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr	Item Number	Mfr Item Name			Effective Date	Version	N	Manufacturing Site		Weight*	UOM	Unit Type	
МС	4LVX4053DR2G	VX4053DR2G LOG CMOS MLTIPLXR			2023-06-08		Р	PH1		142.69	mg	Each	
Manufacturing Proccess Information													
Terminal Plating / Grid Array Material	Terminal Base	Terminal Base Alloy J-STD-020 M			Peak Process Body Temperature Max Time at Pea			Temperature Number of Reflow Cycles					
Matte Tin (Sn) - annealed CU Alloy		1		260 C		С	30	secon	ds 3				
Comments													
level 1 - maximum time at peak temperature durin	g soldering is 10-3	0 seconds											
For more information regarding material composi	ion please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

signs range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	2.73	mg	Supplier	Silicon (Si)	7440-21-3		2.73	mg	
Die Attach	4.85	mg	Supplier	Silver (Ag)	7440-22-4		3.6375	mg	
			Supplier	Epoxy resins	129915-35-1		1.2125	mg	
Lead Frame 75.9	75.92	mg	Supplier	Silver (Ag)	7440-22-4		0.7592	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.1518	mg	
			Supplier	Iron (Fe)	7439-89-6		1.9739	mg	
			Supplier	Copper (Cu)	7440-50-8		73.035	mg	
Mold Compound-Black	55.11	mg		Epoxy Phenol Resin	proprietary data		5.7866	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		49.3234	mg	
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg	
Wire Bond - Au	0.35	mg	Supplier	Gold (Au)	7440-57-5		0.35	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)