

Data sheet | Item number: 706-100/525-100

Connection cable; 25-pole; with solder pin; Male connector; open-ended;
Length: 1 m; Conductor cross-section: 0.25 mm²



www.wago.com/706-100/525-100



Color coding acc. to DIN VDE 47100		25 poles male Sub-D connector	
		Pin number	
White			1
Brown			2
Green			3
Yellow			4
Grey			5
Pink			6
Blue			7
Red			8
Black			9
Violet			10
Grey-Pink			11
Red-Blue			12
White-Green			13
Brown-Green			14
White-Yellow			15
Yellow-Brown			16
White-Grey			17
Grey-Brown			18
White-Pink			19
Pink-Brown			20
White-Blue			21
Brown-Blue			22
White-Red			23
Brown-Red			24
White-Black			25
Shield			Connected to Sub-D

**Data
Notes**

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Cable type	LiYCY
Color code	per DIN VDE 47100

Connection 1

Connector	D-subminiature male connector
Pole number 1	25
Connection type 1	System
Wire cross-section	0.25 mm ²
Connection type	D-subminiature

Connection 2

Connector 2	open-ended
Connection type 2	open-ended

Physical data

Cable length	1 m
--------------	-----

Material Data

Weight	256 g
--------	-------

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	FR

Subject to changes. Please also observe the further product documentation!



GTIN	4055143743884
Customs tariff number	85444290900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-100/525-100	URL	Download
Connection cable; 25-pole; with solder pin; Male connector; open-ended; Length: 1 m; Conductor cross-section: 0.25 mm ²		

Installation Notes

Subject to changes. Please also observe the further product documentation!