# BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD





ATS Part#:

#### ATS-50170B-C1-R0

Description:

17.00 x 17.00 x 7.50 mm BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD

Heat Sink Type: maxiFLOW Heat Sink Attachment: maxiGRIP

Equivalent Part Number:

nber: ATS-50170B-C2-R0 Discontinued

\*Image above is for illustration purpose only.

### **Features & Benefits**

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock and Unpackaged Drop Testing standards
- Comes preassembled with high performance, phase changing, thermal interface material
- Designed for standard height components from 3 to 4.5mm

## **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 18.2 °C/W           | 14.8 °C/W           | 12.8 °C/W           | 11.4 °C/W           | 10.4 °C/W           | 9.7 °C/W            | 9 °C/W              |
|                    | Ducted Flow   | 13.9                | N/A                 | N/A                 | N/A                 | N/A                 | N/A                 | N/A                 |

## **Product Detail**

| Schematic Image                                | Dimension A   | Dimension B           | Dimension C   | Dimension D  | ТІМ  | Finish                                       |
|--|---|-----------------------|---|--|--|--|
|  | 17.00 mm  | 17.00 mm              | 7.50 mm   | 28.4 mm  | T766   | BLUE-ANODIZED                                |
|  | <ul> <li>Dimension</li> <li>ATS-5017         <ul> <li>(Saint Gol</li> <li>Thermal p<br/>application</li> <li>ATS reserve</li> <li>ATS reserve</li> <li>ATS certifier</li> <li>Optional r</li> </ul> </li> </ul> | ves the right to upda | eight from the bottor<br>ct heat sink assembl<br>: Saint Gobain C110<br>provided for referen<br>te or change its proc<br>assembly is RoHS-<br>ion/Removal Tool Se | y with an equivalent<br>OF is discontinued e<br>ice only. Actual perfo<br>lucts without notice t<br>6 and REACH comp<br>et P/N: MGT170 | thermal in<br>ffective 12<br>rmance n<br>o improve | nterface material<br>2/31/10.<br>nay vary by |
| *Image above is for illustration purpose only. |   |                       |   |  |  |  |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), **sales@qats.com** or **www.qats.com**.

© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA



Rev - 011018