# BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape





ATS Part#:

Description:

#### ATS-52250G-C1-R0

25.00 x 25.00 x 12.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape

Heat Sink Type:maxiFLOWHeat Sink Attachment:Thermal TapeEquivalent Part Number:ATS-52250G-C2-R0

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- maxiFLOW<sup>™</sup> design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

### **Thermal Performance**

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	5.2 °C/W	4.1 °C/W	3.6 °C/W	3.2 °C/W	2.9 °C/W	2.7 °C/W	2.6 °C/W
	Ducted Flow	4	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	25.00 mm	25.00 mm	12.50 mm	44.94 mm	T412	BLUE-ANODIZED
	<ul> <li>Dimension</li> <li>ATS-5225</li> <li>(Saint-Gol</li> <li>Thermal p application</li> <li>ATS resen performant</li> <li>ATS certification</li> </ul>	i0G-C2-R0 is the exa bain C675). performance data are n. rves the right to upda ace. ies that this heat sin	omponent size. leight from the bottor act heat sink assemb e provided for referer ate or change its prod k assembly is RoHS listom options availab	bly with an equivalen nce only. Actual perf ducts without notice -6 and REACH com	t thermal ormance to improv	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), **sales@qats.com** or **www.qats.com**.

