

PRODUCT FAMILY DATASHEET JENNY

JENNY

Silicone lenses designed for sports field, area and canopy lighting and compatible with up to 7070 size LED packages, CSP clusters and up to 11 mm LES size COBs.

LEDiL was the first in the world to launch a mass-produced LED silicone optic by introducing the JENNY-family. Designed for street and area lighting such as high masts to meet the strictest standards in lighting sport fields, airports and harbours. The latest JENNYs come with no spilling light backwards or upwards, and are optimized for the latest ultra-high-power LEDs typically producing over 90 % efficiency. High thermal capabilities of silicone ensure your products will last for years. All JENNY optics can be ordered as single lenses or in 8X1 arrays with an optional frame for screw installation.




JENNY

35 x 35 mm single lenses

PRODUCTS:


F15382_JENNY-CY-G2



Dimensions: 35.0 mm x 35.0 mm Height: 11.50 mm

~105° + 105° batwing light distribution for canopy and symmetrical tunnel lighting.


F14563_JENNY-T4



Dimensions: 35.0 mm x 35.0 mm Height: 17.02 mm

IESNA Type IV light distribution for wider roads and large outdoor areas. Variant with wire channels on the sides enabling compatibility with small COBs.

F14531_JENNY-CY



Dimensions: 35.0 mm x 35.0 mm Height: 11.50 mm


~105° + 105° batwing light distribution for canopy and symmetrical tunnel lighting. Variant with wire channels on the sides enabling compatibility with small COBs.



PRODUCT FAMILY DATASHEET JENNY

PRODUCTS:

F15909_JENNY-FT65




Dimensions: 35.0 mm x 35.0 mm

Height: 15.35 mm

Forward throwing beam with peak in 65°

F15596_JENNY-FT45




Dimensions: 35.0 mm x 35.0 mm

Height: 20.65 mm

Forward throwing beam with peak in 45°

F15541_JENNY-60




Dimensions: 35.0 mm x 35.0 mm

Height: 13.42 mm

~60° beam

F15539_JENNY-40




Dimensions: 35.0 mm x 35.0 mm

Height: 15.00 mm

~40° beam

F15538_JENNY-20




Dimensions: 35.0 mm x 35.0 mm

Height: 14.52 mm

~20° beam

F15383_JENNY-T4-G2



Dimensions: 35.1 mm x 35.1 mm

Height: 17.00 mm

IESNA Type IV light distribution for wider roads and large outdoor areas.



PRODUCT FAMILY DATASHEET JENNY

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy